Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	1 of 19



1. IDENTIFICATION OF THE SUBSTRATE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name/designation: Euroroof PU Primer / Sealer.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Adhesive / Primer.

1.3 Supplier details

Alumasc Building Products Ltd White House Works, Bold Road, Sutton, St Helens, Merseyside, United Kingdom, WA9 4JG Tel: +44 (0)1744 648400 e-mail: <u>technical@alumascroofing.com</u>

1.4 Emergency telephone number

Association / Organisation:National Poisons Information Service Emergency telephone numbers:0344 892 0111 (Healthcare professionals only) Other emergency telephone numbersAlumasc Building Products: +44 17 4464 8400 (Mon-Thurs – 08.30-17.00 Fri – 08.30-16.00)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Considered a hazardous mixture according to Reg. (EC) No 1272/2008 and their amendments. Classified as Dangerous Goods for transport purposes.

Classification according to Regulation (EC) No. 1272/2008 [CLP][1]:

H226 - Flammable Liquids Category 3, H336 - Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, H411 – Hazardous to the Aquatic Environment Long-Term Hazard Category 2, H372 - Specific Target Organ Toxicity - Repeated Exposure Category 1, H304 - Aspiration Hazard Category 1. Legend:

1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567.

2.2 Label elements

Hazard pictures:

Sianal word:

Hazard statements:



H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H312 Harmful in contact with skin.
H373 May cause damage to organs through prolonged or repeated exposure.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.

Supplementary statements:

EUH204 Contains isocyanates. May produce an allergic reaction.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	2 of 19



Precautionary statements prevention:	 P201 Obtain special instructions before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe mist/vapours/spray. P271 Use only a well-ventilated area. P280 Wear protective gloves, protective clothing, eye protection and face protection. P284 [In case of inadequate ventilation] wear respiratory protection. P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment. P242 Use non-sparking tools. P243 Take action to prevent static discharges. P264 Wash all exposed external body areas thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace.
Precautionary statements response:	 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P313 IF exposed or concerned: Get medical advice/ attention. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor/ physician/first aider. P370+P378 In case of fire: Use alcohol resistant foam or normal protein foam to extinguish. P302+P352 IF ON SKIN: Wash with plenty of water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER/doctor/physician/first aider/if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
Precautionary statements storage:	P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.
Precautionary statements disposal:	P501: Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

2.3 Other hazards

Methylene Chloride:	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply).
Xylene:	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply).
Polymeric Diphenylmethane:	Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply).
Diisocyanate:	

3. COMPOSITION AND INFORMATION ABOUT THE COMPONENTS

3.1 Substances

See 'Composition on ingredients' in Section 3.2.

3.2 Mixtures

1. CAS No 2. EC No 3. Index No 4. REACH No	% [weight]	Name	Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	Nanoform Particle Characteristics
1. 1330-20-7 2. 215-535-7 3. 601-022-00-9 4. Not available	60-90	Xylene *	Flammable Liquid Category 3, Acute Toxicity (Dermal) Category 4, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2; H226, H312, H332, H315 [2]	Not available

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	3 of 19



1. 9016-87-9 2. Not available 3. Not available 4. Not available	10-30	Polymeric Diphenylmethane Diisocyanate	Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2, Skin Sensitizer Category 1, Respiratory Sensitizer Category 1, Carcinogenicity Category 2, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Specific target organ toxicity - repeated exposure Category 2; H332, H315, H319, H317, H334, H351, H335, H373, EUH204 [1]	Not available
Legend:	1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567; 3. Classification drawn from C&L * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties.			

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye contact:	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin contact:	If skin contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation:	If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Following uptake by inhalation, move person to an area free from risk of further exposure. Oxygen or artificial respiration should be administered as needed. Asthmatic-type symptom
Ingestion:	If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice. Avoid giving milk or oils. Avoid giving alcohol.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11.

 Reference No:
 SDS-AP006
 Version:
 2.1

 Date of issue:
 27/05/2025
 Page:
 4 of 19



4.3 Indication of any immediate medical attention and special treatment needed.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For sub-chronic and chronic exposures to isocyanates:

This material may be a potent pulmonary sensitiser which causes bronchospasm even in patients without prior airway hyperreactivity.

Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts.

Conjunctival irritation, skin inflammation (erythema, pain vesiculation) and gastrointestinal disturbances occur soon after exposure.

Pulmonary symptoms include cough, burning, substernal pain and dyspnoea.

Some cross-sensitivity occurs between different isocyanates.

Noncardiogenic pulmonary oedema and bronchospasm are the most serious consequences of exposure. Markedly symptomatic patients should receive oxygen, ventilatory support and an intravenous line.

Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.

Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.

Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.

There is no effective therapy for sensitised workers.

[Ellenhorn and Barceloux; Medical Toxicology]

NOTE: Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the concentration and duration of exposure. They induce smooth muscle contraction which leads to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity.

[Karol & Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992]

Personnel who work with isocyanates, isocyanate prepolymers or polyisocyanates should have a pre-placement medical examination and periodic examinations thereafter, including a pulmonary function test. Anyone with a medical history of chronic respiratory disease, asthmatic or bronchial attacks, indications of allergic responses, recurrent eczema or sensitisation conditions of the skin should not handle or work with isocyanates. Anyone who develops chronic respiratory distress when working with isocyanates should be removed from exposure and examined by a physician. Further exposure must be avoided if a sensitivity to isocyanates or polyisocyanates has developed.

For acute or short term repeated exposures to Xylene:

Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.

Pulmonary absorption is rapid with about 60-65% retained at rest.

Primary threat to life from ingestion and/or inhalation, is respiratory failure.

Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 < 50 mm Hg or pCO2 > 50 mm Hg) should be intubated.

Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.

A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.

Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

BIOLOGICAL EXPOSURE INDEX - BEI.

5. FIRE-FIGHTING MEASSURES

5.1 Extinguishing media

Small quantities of water in contact with hot liquid may react violently with generation of a large volume of rapidly expanding hot sticky semi-solid foam.

Presents additional hazard when fire fighting in a confined space.

Cooling with flooding quantities of water reduces this risk.

Foam.

Dry chemical powder.

BCF (where regulations permit).

 Reference No:
 SDS-AP006
 Version:
 2.1

 Date of issue:
 27/05/2025
 Page:
 5 of 19



5.2 Special hazards arising from the substance or mixture

Fire incompatibility:

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

5.3 Advice for fire-fighters

Fire-fighting:

Alert fire brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus.

Fire/explosion hazard:

Liquid and vapour are flammable. Moderate fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Combustion products include:

- Carbon Monoxide (CO)

- Carbon Dioxide (CO2)
- Isocyanates
- Hydrogen cyanide
- Minor amounts of Nnitrogen oxides (NOx)
- Other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions. When heated at high temperatures many isocyanates decompose rapidly generating a vapour which pressurises containers, possibly to the point of rupture. Release of toxic and/or flammable isocyanate vapours may then occur Burns with acrid black smoke.

6. ACCIDENTIAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

See Section 8.

6.2 Environmental precautions

See Section 12.

6.3 Methods and material for containment and cleaning up

Minor spills:

Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes.

Major spills:

Liquid Isocyanates and high isocyanate vapour concentrations will penetrate seals on self contained breathing apparatus -SCBA should be used inside encapsulating suit where this exposure may occur.

For isocyanate spills of less than 40 litres (2 m2):

Evacuate area from everybody not dealing with the emergency, keep them upwind and prevent further access, remove ignition sources and, if inside building, ventilate area as well as possible.

Notify supervision and others as necessary.

Put on personal protective equipment (suitable respiratory protection, face and eye protection, protective suit, gloves and impermeable boots).

Avoid contamination with water, alkalies and detergent solutions.

Material reacts with water and generates gas, pressurises containers with even drum rupture resulting. DO NOT reseal container if contamination is suspected.

Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

May be violently or explosively reactive.

Reference No:SDS-AP006Version:2.1Date of issue:27/05/2025Page:6 of 19



6.4 Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Safe handling:

Containers, even those that have been emptied, may contain explosive vapours.

Do NOT cut, drill, grind, weld or perform similar operations on or near containers.

Electrostatic discharge may be generated during pumping - this may result in fire.

Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until fill pipe submerged to twice its

diameter, then <= 7 m/sec).

Contains low boiling substance:

Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately. Check for bulging containers.

Vent periodically.

Always release caps or seals slowly to ensure slow dissipation of vapours.

Avoid all personal contact, including inhalation.

Wear protective clothing when risk of overexposure occurs.

Use in a well-ventilated area.

Fire & explosion protection:

See Section 5.

Other information:

Store in original containers in approved flammable liquid storage area.

Store away from incompatible materials in a cool, dry, well-ventilated area.

DO NOT store in pits, depressions, basements or areas where vapours may be trapped.

for commercial quantities of isocyanates:

Isocyanates should be stored in adequately bunded areas. Nothing else should be kept within the same bunding. Prepolymers need not be

segregated.

7.2 Conditions for safe storage, including any incompatibilities

Suitable container:

Packing as supplied by manufacturer.

Plastic containers may only be used if approved for flammable liquid.

Check that containers are clearly labelled and free from leaks.

For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner

package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt.

Storage incompatibility:

Xylenes:

- May ignite or explode in contact with strong oxidisers, 1,3-dichloro-5,5-dimethylhydantoin, uranium fluoride.
- Attack some plastics, rubber and coatings.
- May generate electrostatic charges on flow or agitation due to low conductivity.
- Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents.
- Aromatics can react exothermically with bases and with diazo compounds.

For Alkyl Aromatics:

The alkyl side chain of aromatic rings can undergo oxidation by several mechanisms. The most common and dominant one is the attack by:

- Oxidation at benzylic carbon as the intermediate formed is stabilised by resonance structure of the ring.
- Following reaction with oxygen and under the influence of sunlight, a hydroperoxide at the alpha-position to the aromatic ring, is the primary.
- Oxidation product formed (provided a hydrogen atom is initially available at this position) this product is often short-lived but may be stable.
- Dependent on the nature of the aromatic substitution; a secondary C-H bond is more easily attacked than a primary C-H bond whilst a tertiary C-H bond is even more susceptible to attack by oxygen.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	7 of 19



- Monoalkylbenzenes may subsequently form monocarboxylic acids; alkyl naphthalenes mainly produce the corresponding naphthalene.
- Carboxylic acids.

Avoid reaction with water, alcohols and detergent solutions. Isocyanates are electrophiles, and as such they are reactive toward a variety of nucleophiles including alcohols, amines, and even water. Upon treatment with an alcohol, an isocyanate forms a urethane linkage.

- A range of exothermic decomposition energies for isocyanates is given as 20-30 kj/mol.
- The relationship between energy of decomposition and processing hazards has been the subject of discussion; it is suggested that values of
- Energy released per unit of mass, rather than on a molar basis (J/g) be used in the assessment.
- For example, in "open vessel processes" (with man-hole size openings, in an industrial setting), substances with exothermic decomposition
- Energies below 500 J/g are unlikely to present a danger, whilst those in "closed vessel processes" (opening is a safety valve or bursting disk)
- Present some danger where the decomposition energy exceeds 150 J/g.

						Red A
+	x	+	x	+	+	+

- **X** Must not be stored together.
- **O** May be stored together with specific preventions.
- + May be stored together.

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

7.3 Specific end uses(s)

See Section 1.2.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Ingredient	DNELS	PNECs
Xylene:	Exposure Pattern Worker Dermal 212 mg/kg bw/day (Systemic, Chronic) Inhalation 221 mg/m ³ (Systemic, Chronic) Inhalation 221 mg/m ³ (Local, Chronic) Inhalation 442 mg/m ³ (Systemic, Acute) Inhalation 442 mg/m ³ (Local, Acute) Dermal 125 mg/kg bw/day (Systemic, Chronic) * Inhalation 65.3 mg/m ³ (Systemic, Chronic) * Oral 12.5 mg/kg bw/day (Systemic, Chronic) * Inhalation 65.3 mg/m ³ (Local, Chronic) * Inhalation 260 mg/m ³ (Local, Acute) * Inhalation 260 mg/m ³ (Local, Acute) *	0.327 mg/L (Water (Fresh)) 0.327 mg/L (Water - Intermittent release) 0.327 mg/L (Water - Intermittent release) 0.327 mg/L (Water (Marine)) 12.46 mg/kg sediment dw (Sediment (Fresh Water)) 12.46 mg/kg sediment dw (Sediment (Marine)) 2.31 mg/kg soil dw (Soil) 6.58 mg/L (STP)

* Values for general population.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	8 of 19



Occupational Exposure Limits (OEL):

Ingredient data:

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)	Xylene	Xylene (mixed isomers, pure)	50 ppm / 221 mg/m3	442 mg/m3 / 100 ppm	Not available	Skin
UK Workplace Exposure Limits (WELs)	Xylene	Xylene, o-,m-,p- or mixed isomers	50 ppm / 220 mg/m3	441 mg/m3 / 100 ppm	Not available	sk, BMGV
Europe ECHA Occupational exposure limits - Activity list	Polymeric Diphenylmet- hane Diisocyanate	Not available	Not available	Not available	Not available	Not available
UK Workplace Exposure Limits (WELs)	Polymeric Diphenylmet- hane Diisocyanate	Isocyanates, all (as -NCO) except M ethyl Isocyanate	0.02 mg/m3	0.07 mg/m3	Not a available	Sen

Emergency limits:

Ingredient	TEEL-1	TEEL-2	TEEL-3
Xylene	Not available	Not available	Not available
Polymeric Diphenylmethane Diisocyanate	0.15 mg/m3	3.6 mg/m3	22 mg/m3

Ingredient	Original IDLH	Revised IDLH
Xylene	900 ppm	Not available
Polymeric Diphenylmethane	Not available	Not available
Diisocyanate		

8.2 Exposure controls

8.2.1. Appropriate engineering Controls:	CARE: Use of a quantity of this material in confined space or poorly ventilated area, where rapid build up of concentrated atmosphere may occur, could require increased ventilation and/or protective gear. Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. All processes in which isocyanates are used should be enclosed wherever possible. Total enclosure, accompanied by good general ventilation, should be used to keep atmospheric concentrations below the relevant exposure standards. If total enclosure of the process is not feasible, local exhaust ventilation may be necessary.
8.2.2. Personal protection:	
Eye and face protection:	Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection:	See Hand Protection below.
Hands/feet protection:	NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. Do NOT wear natural rubber (latex gloves).

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	9 of 19



	Isocyanate resistant materials include Teflon, Viton, nitrile rubber and some PVA gloves. Protective gloves and overalls should be worn as specified in the appropriate national standard. Contaminated garments should be removed promptly and should not be re-used until they have been decontaminated. DO NOT use skin cream unless necessary and then use only minimum amount. Isocyanate vapour may be absorbed into skin cream and this increases hazard.
Body protection:	See Other Protection below.
Other protection:	All employees working with isocyanates must be informed of the hazards from exposure to the contaminant and the precautions necessary to prevent damage to their health. They should be made aware of the need to carry out their work so that as little contamination as possible is produced, and of the importance of the proper use of all safeguards against exposure to themselves and their fellow workers. Adequate training, both in the proper execution of the task and in the use of all associated engineering controls, as well as of any personal protective equipment, is essential. Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered.

Recommended material(s):

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer generated selection: Euroroof PU Primer / Sealer.

Materia	CPI	Materia	CPI	
PE/EVAL/PE	A	NATURAL+NEOPRENE	С	
PVA	А	NEOPRENE	С	
TEFLON	A	NEOPRENE/NATURAL	С	
VITON	A	NITRILE	С	
BUTYL	С	NITRILE+PVC	С	
BUTYL/NEOPRENE	С	PVC	С	
HYPALON	С	PVDC/PE/PVDC	С	
NAT+NEOPR+NITRILE	С			

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Respiratory protection:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent) For spraying or operations which might generate aerosols:

Full face respirator with supplied air.

- In certain circumstances, personal protection of the individual employee is necessary. Personal protective devices should be regarded as being supplementary to substitution and engineering control and should not be used in preference to them as they do nothing to eliminate the hazard.
- However, in some situations, minimising exposure to isocyanates by enclosure and ventilation is not possible, and occupational exposure standards may be exceeded, particularly during on-site mixing of paints, spray-painting, foaming and maintenance of machine and ventilation systems. In these situations, air-line respirators or
- Self-contained breathing apparatus complying with the appropriate nationals standard must be used.
- Organic vapour respirators with particulate pre-filters and powered, air-purifying respirators are NOT suitable.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	10 of 19



- Personal protective equipment must be appropriately selected, individually fitted and workers trained in their correct use and maintenance. Personal protective equipment must be regularly checked and maintained to ensure that the worker is being protected.
- Air- line respirators or self-contained breathing apparatus complying with the appropriate national standard should be used during the clean-up of spills and the repair or clean-up of contaminated equipment and similar situations which cause emergency exposures to hazardous atmospheric concentrations of isocyanate.

8.2.3. Environmental exposure controls

See Section 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Important health, safety and environmental information

Appearance: Physical state:	brown Liquid	Relative density (Water = 1):	0.9-1.0
Odour:	Not available	Partition coefficient n-octanol/water:	Not available
Odour threshold: pH (as supplied): Melting point/freezing point (°C):	Not available Not available Not available	Auto-ignition temperature (°C): Decomposition temperature: Viscosity (cSt):	Not available Not available 105.263-526.316
Initial boiling point and boiling ranae (°C):	>35	Molecular weight (g/mol):	Not available
Flash point (°C):	>30	Taste:	Not available
Evaporation rate:	Not available	Explosive properties:	Not available
Flammability:	Flammable.	Oxidising properties:	Not available
Upper Explosive Limit (%):	Not available	Surface Tension (dyn/cm or mN/m):	Not available
Lower Explosive Limit (%):	Not available	Volatile Component (%vol):	Not available
Vapour pressure (kPa):	Not available	Gas group:	Not available
Solubility in water:	Not available	pH as a solution (1%):	Not available
Vapour density (Air = 1):	Not available	VOC g/L:	Not available
Nanoform Solubility: Particle Size:	Not available Not available	Nanoform Particle Characteristics:	Not available 0.9-1.0

9.2 Other information

This product contains a maximum VOC content of 78%.

10. STABILITY AND REACTIVITY

10.1 Reactivity

See Section 7.2.

10.2 Chemical stability

Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.

10.3 Possibility of hazardous reactions

See Section 7.2.

10.4 Conditions to avoid

See Section 7.2.

10.5 Incompatible materials

See Section 7.2.

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

SDS-AP006 27/05/2025 2.1 11 of 19 Reference No: Version: Date of issue: Page:



10.6 Hazardous decomposition products

See Section 5.3.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

The material can cause replicatory initiation in some persons. The body's response to such initiation can cause further lung damage. Inhabition of vopous may cause dowiness and diziness. This may be accompanied by sleepiness, reduced clefiness, loss of reflexes, lack of co-ordination, and verigo. The material may Dee not solite by CD Directives or other classification systems as "harmful by inhabition". This is because of the lack of comboarding animal or human evidence. Inhabition hazard is increased at higher femperatures. The vapour/mist may be highly irificiting to the upper respiratory fract and lungs; the response may be severe enough to produce bronchils and pulmonary octema. Possible neurological symptoms arising from locyanate exposure include headache, insomnia, euphoria, cataja, andely neurosis, depression and paranalo. Castrointestinal distrubances are characteristed by nouse and womfing, inhalation of high concentrations of gas/vapour causes lung irititation with coughing and noused, contrait nervous depression with headache and diziness, slowing of reflexes, fatigue and incordination. Inholed: unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asplication. This may happen with tittle warming of overseposure. The use of a quantity of material in an unventilated ar confined space may result in increased exposure base and largelines. Relatively small amounts absorbed from the lungs may prove to a directing atmosphere developing. Before starting consider control of exposure by machanical ventiling atmosphere developing. Before starting consider control of exposure by mochanical ventiling atmosphere adverses. Relatively small amounts absorbed from the lungs may prove to a mothasite sy asplant tos abios. Relatively small amounts absorbed fro		Inere is strong evidence to suggest that this material can cause, it inhaled once, very serious, irreversible damage of organs
 Inhaldion of Vapours may cause drowsiness and diziness. This may be accompanied by sleepiness, treduced alertness, loss of reflexes, lack of co-ordination, and vertigo. The enterial has NOT been classified by CD Directives or other classification systems as "harmful by inhalation". This is because of the lack of comoborating animal or human evidence. Inhalation hazard is increased at higher temperatures. The vapour/mist may be highly initiating to the upper respiratory fract and lungs: the response may be severe enough to produce bronchils and pulmorary oderma. Possible neurological symptoms or sing from isocyanate exposure include headache, insomnia, euphania, activatio, anviety neurosis, depression and paranola. Gostrointestinal disturbances are characterised by nausea and vomiling. Inhalation of high concentrations of gar/vapour causes lung initiation with coughing and nauses, central nervous depression with headache and dizaness, stowing of reflexes, foligue and inco-ordination. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventified areas. The vapour may displace and replace ari in breathing zone, acting as a simple asphyxiant. This may happen with little worning of overexposure. The use of a quantity of material in an unventificated or confined space may result in increased exposure and an initiating atmosphere developing. Before starting consider control of exposure by machanical ventilation. Headache, faligue, firedness, initability and digestive disturbances (nause, loss of appetite and bioating) are the mass. Relatively small amounts, absorbed from the lungs may prove fatal. Inhalation of acrosis (mists, fumes), generated by the material during the cause of normal handing, may produce severely taxic. Relatively small amounts, absorbed from the lungs may prove fatal. Indection taxic as the vapoure and papethene in a cleain of otwelbeing, confusion, dizzin		The material can cause respiratory irritation in some persons. The body's response to such irritation
Indiction of vapours may cause drowaness and diziness. Inis may be accompanied by steepiness, reduced alertness, loss of reflexes, lack of co-robrating animal or human evidence. Inhalation: This is because of the lack of corobrating animal or human evidence. Inhalation hazard is increased at higher temperatures. The vapour/msit may be highly inflating to the upper respiratory tract and lungs; the response may be severe enough to produce bronchits and pulmonary oedema. Possible neurological symptoms arising from isocyrandle exposure include headchee, insominia, euphoria, ataxia, anxiety neurosis, depression and paranola. Gastrointestinal disturbances are characterised by noused and vomiting, inhalation of high concentrations of gas/vapour causes lung inflation with coughing and nousea, central nervous depression with headcache and diziness, slowing of reflexes, fatigue and inco- ordination. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unvertiliated areas. The vapour may displace and repression: The trade as a simple asphysion. This may happen with little warning of overexposure. The use of a quantity of material in an unventiliated or confined space may result in increased exposure and an initiating atmosphere developing. Before starting consider control of exposure by mechanical ventilating. Interdets (matus, interdets), intability and digestive disturbances (nausea, loss of appetite and bloating) are the mast common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system thas also been noted amongst workes. Xylene is a central nervous system depression of deud by central nervous system depression function of enorsols (mist, truns), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs with the risk of chemical previous conserseurces may result. (ICSC13733) The material has NOT been classified by EC Directives or othera classified in tere ind		can cause further lung damage.
Indextee default has NOT been classified by EC Directives or other classification systems as "hamful by inhalation". This is because of the tack of comoborating animal or human evidence. Inhalation hazard is increased at higher temperatures. The vapour/mist may be highly initiating to the upper respiratory tract and lungs; the response may be severe enough to produce bronchits and pulmonary oedema. Possible neurological symptoms arising from isocyanate exposure include headache, insomnia, euphoria, ataxia, anxiety neurosis, depression and paranonia. Gastrointestinal distributances are characterised by nause and vances, a central nervous depression with headache and diziness, slowing of reflexes, fatigue and inco-ordination. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventitated areas. The vapour may displace and replace ari in breathing zone, acting as a simple asphysiant. This may happen with little warning of overexposure. Inverse and inco-ordination. Headache, fatigue, itredness, initability and digestive disturbances (nausea, loss of appetite and biooling) are the mays accommon symptoms of xystem overexposure. Inverse the average area and an envolve system has also been noted amongs workers. Xylene is a central nervous system depressant. Inhalation of meritability and digestive disturbances (nausea, loss of appetite and biooling) are the may also be an oted amongs workers. Xylene is a central nervous system depressant. Inhalation the lungs may prove tatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of head, cold an umbess, Miching, Itemats, edpression of breathing, and arest. The vapour depression of breathing, and arest. The vapour depression of breathing and arest. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symp		Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertice.
inholotion*. This is because of the lock of corrobording animal or human evidence. Inholotion hazard is increased at higher temperatures. The vapour/mist may be highly inflating to the upper respiratory tract and lungs; the response may be severe enough to produce branchils and pulmonary oedema. Possible neurological symptoms ansing from isocyanate exposure include headche, insomina, euphonia, attaki, anxiety neurosis, depression and paranola. Gastrointestinal distributances are characterised by nausea and vomiting, inholation of high concentrations of gas/vapour causes lung inflation with coughing and nausea, central nervous depression with headcabe and diziness, slowing of reflexes, fatigue and inco- ordination. Material is highly volatile and may quickly form a concentrated atmosphere in confined on unventilated areas. The vapour may displace and replace ain therasthing zone, acting as a simple asphysiant. This may happen with little warning of overexposure. The use of a quantify of material in an unventilited or confined space may result in increased exposure and an initiating atmosphere developing. Before starting consider control of exposure by mechanical ventiliation. Headcache, fatigue, tiredness, initability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of kylene overexposure. Injury to the heart, liver, kidneys and nervous system thes also been noted amorgst workers. Xylene is a central nervous system depressant Inholation of aeroso (mists, fumas), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. Ingestion: The acute toxicity of inholed alkylbenzene is best desclibed by central nervous system depression. These compounds m		The material has NOT been classified by FC Directives or other classification systems as "harmful by
Inhalation hazard is increased at higher temperatures. The vapour/mist may be highly initiating to the upper respiratory tract and lungs: the response may be severe enough to produce branchils and pulmonary oedema. Possible neurological symptoms arising from isocyanate exposure include headache, insomna, euphoria, ataxia, anxiety neurosis, depression and parenala. Gastraintestinal disturbances are characterised by nausea and vomiting, inhalation of high concentrations of gas/vapour causes lung imitation with coughing and nausea, centration is socyanate expension with headache and dizzness, slowing of reflexes, fatigue and inco-ordination. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphysiant. This may happen with ittle warning of overexposure. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an iritrating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Headache, fatigue, liredness, initability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xilene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers. Xylene is a central nervous system depression The acute toxicity of inholed disturbances is best described by central from the lungs may prove fatal. The caute toxicity of inholed distored and aspheres. Underline accute toxicity of inholed distored any cause and areasing include light-headedness, nerevousnes, depression of breathing, and arest.		inhalation". This is because of the lack of corroborating animal or human evidence.
Inhelicity of some server enough to produce bronchills and pulmonary ocedema. Possible neurological symptoms arising from isocyanate exposure include headache, insomnia, eupohaia, ataxia, anxiety neurosis, depression and paranola. Gastrointestinal disturbances are characterised by nausea and voniting, inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizzness, slowing of reflexes, fatigue and inco- ordination. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphysiant. This may happen with little warning of overexposure. The use of a quantity of material in an unventilated areas, and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Headache and digetive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers. Xylene is a central nervous system depressant Inhalation of aerosols (miss, fumas), generated by the material during the course of normal handling. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may dis act as general ancesthelics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, diziness, drowiness, inging in the eas, blured or double vision, vomiting and sensations of heat, cold or numbness. Witching, termors, somequences may result, licCaI3733). There is strong evidence to suggest that this material can cause, if swallowed once, very serious, inversible domage of organs. Swallowing of the liquid may cause apiration into the lungs with the risk of chemical pneuromating; serious consequences may result, licCaI3733]. There		Inhalation hazard is increased at higher temperatures.
be severe enough to produce branchins and pulmonary oedema. Possible neurological symptoms arising from isocyanate exposure include headache, insomia, eupharia, actavia, anxiety neurosis, depression and paranoia. Gastraintestinal disturbances are characterised by nausea and vomiting, inhalaction of high concentrations of gas/yapour causes lung iritation with coughing and nausea, central nervous depression with headache and diziness, slowing of reflexes, fatigue and inco- ordination. Inhaled: Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphysiant. This may happen with ittle worning of overexposure. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an intrating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Headache, fatgue, firedness, initability and digestive disturbances (nausea, lass of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system thas also bae noted amongst workers. Xylene is a central nervous system depressant inhalation of aerosols (mist, furnes), generated by the material during the course of normal handling, may produce severely toxic effects. Relotively small meanus absorbed from the lungs may prove fatal. The caute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general ancesthetics. Whole body symptoms of poisoning include light-headedness, wollching of the light may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The		The vapour/mist may be highly irritating to the upper respiratory tract and lungs; the response may
Instruction Bocyatanoia. Gastioninestinal disturbances are characterised by nausea and vomiting, Inhalation of high concentrations of gas/vapour causes lung initiation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco- ordination. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphysiant. This may happen with little warning of overexposure. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an initiating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Headache, fatigue, tiredness, initiability and digestive disturbances (nausea, lass of appetite and bloating) are the most common symptoms of xylene overxposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers. Xylene is a central nervous system depressant Inhalation of acrossol (mists, furmes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general concesthelics. Whole body symptoms of poisoning include light-headedness, nervousness, depression of breathing, and arest. There is strong eydence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may causental the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal. Inpert		be severe enough to produce bronchitis and pulmonary oedema. Possible neurological symptoms
Inhabition of high concentrations of gas/vapour causes lung initiation with coughing and nause, central nervous depression with headache and diziness, slowing of reflexes, fatigue and inco- ordination. Inhaled: Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace are in breathing zone, acting as a simple asphyxiant. This may happen with little warning of overexposure. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an initating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Headache, fatigue, tiredness, initability and digestive disturbances (naused, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers. Xylene is a central nervous system depressant Inhalation of acrosols (mists, furnes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The ocute toxicity of inhaled akylbenzene is best described by central nervous system depression. Unshess, hintching, tremors. convulsions, unconsclousness, apprehension, a feeling of weil-being, confusion, diziness, drowsiness, finging in the ears, butred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors. ingestion: There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may		depression and parapola. Gastrointestinal disturbances are characterised by nausea and vomitina
Inhaled: central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco- ordination. Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace all in breathing zone, acting as a simple asphywiant. This may happen with little ware and replace all in breathing zone, acting as a simple asphywiant. This may happen with little ware and replace all in breathing zone, acting as a simple asphywiant. This may happen with little ware and replace all in breathing zone, acting as a simple asphywiant. This may happen with little ware and replace all in breathing all soce may result in increased exposure and an initrating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Headache, fatigue, litedness, initability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system tos also been noted amongst workers. Xylene is a central nervous system depressont Inhaldrion of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowiness, inging in the ears, blurred or double vision, vomiling and sensations of heat, cold or numbness, twitching, tremors. Ingestion: There is strong evide		Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea,
Inhaled: Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphysiant. This may happen with title warning of overexposure. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an initiating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Headache, fatigue, tiredness, initability and digestive disturbances (nausea, loss of appetite and bloating) are the mast common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted atmongst workers. Xylene is a central nervous system depressant Inholation of acrosols (mist, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervourses, apprehension, a feeling of well-being, confusion, diziness, drowsiness, tringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors. convulsions, lunconsciousness, depression of breathing, and arrest. There is strong evidence to suggest that this material can cause, if svallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis serious correspong animal or human evidence. Accidental ingestion of the lack of corroborating animal or human evidence. Accidental ingestion of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that		central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-
Inhaled: Material is highly volatile and may quickly form a concentrated atmosphere in contined of unvertillated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphysiant. This may happen with little warning of overexposure. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Headache, fotigue, tiredness, irritability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted armongst workers. Xylene is a central nervous system depressant Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also acit as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, burred or double vision, vomiting and sensations of heat, cold or numbness. twitching, thermos, convulsions, unconsciousness, depression of breathing, and arrest. Ingestion: There is strong evidence to suggest that this material can cause, if swallowed once, very serious, ineversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences more yresult, IC		ordination.
 Indect. Invertidied dress, the vapoen with little warning of overexposure. The use of a quantify of material in an unventilated or confined space may result in increased exposure and an iritiating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Headache, faligue, liredness, irritability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers. Xylene is a central nervous system depressant Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, diziness, drowsiness, inging in the ears, blured or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors. convulsions, unconsciousness, depression of breathing, and arrest. Ingestion: Ingestion: Ingestion: Ingestion: Ingestion: Ingestion: Skin contact is not thought to have harmful health effects (as classified under C. Directives); the material may still produce health damage following entry through wounds, lesions arbarsions. Open cuts, abraded or initiated skin should not be exposed to this material and ensure that any settions is not thought to have harmful health effects (as classified under EC Directives); t	Inhalad	Material is highly volatile and may quickly form a concentrated atmosphere in contined or
Ingestion: The use of a quantity of material in an unvertilited or confined space may result in increased exposure and an initiating atmosphere developing. Before starting consider control of exposure by mechanical vertilition. Headache, fatigue, tiredness, initability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers. Xylene is a central nervous system depressant Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, finging in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Inset is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of tess skin contact: There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, ir	ininalea.	asphysiant. This may happen with little warning of overexposure
exposure and an intrating atmosphere developing. Before starting consider control of exposure by mechanical ventilation. Headache, fatigue, firedness, irritability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers. Xylene is a central nervous system depressant Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fotal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizzness, drowiness, rigning in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors. convulsions, unconsciousness, depression of breathing, and arrest. There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause asplication into the lungs with the risk of chemical pneumonilit; serious consearguences may real. (LCSCI373) There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dematilits condition Skin contact: There is not thought to have harmful health effects (as classified under EC Directives); the material may still produce he		The use of a quantity of material in an unventilated or confined space may result in increased
Ingestion: mechanical ventilation. Headache, fotigue, firedness, irritability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers. Xylene is a central nervous system depressant Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, convulsions, unconsclousness, depression of breathing, and arrest. Convulsions, unconsclousness, depression of breathing, and arrest. There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal. Skin contact: Skin contact is not thought to have h		exposure and an irritating atmosphere developing. Before starting consider control of exposure by
Ingestion: Ingestion: Ingestion: Ingestion: Skin contact: Skin contact: Ski		mechanical ventilation.
and nervous system has also been noted amongst workers. Xylene is a central nervous system depressant Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal. Skin contact: Entry into the bold-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material condition Skin contact: Entry into the blod-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the mat		headache, faligue, firedness, irritability and algestive disturbances (naused, loss of appellie and bloating) are the most common symptoms of xylene overexposure. Injury to the heart liver, kidneys
Xylene is a central nervous system depressant Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Ingestion: There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC1373) Ingestion: There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC1373) In material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of coroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal. Skin contact: There is strong evidence to suggest that this		and nervous system has also been noted amongst workers.
Inhalation of aerosols (mist, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Ingestion: There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal. Skin contact: There is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Skin contact: Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the materia		Xylene is a central nervous system depressant
Ingestion: may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal. Skin contact: There is strong evidence to suggest that this material may accentuate any pre-existing dermatilits condition Skin contact: Entry into the blood-stream, through, for example, cuts, abracions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Skin contact: Entry into the blood-stream, through, for example, cuts, abracisons or abrasions. Copen cuts, abraded or irritated skin should not be use of the material and ensure that any external damage is suitably protected. </td <td></td> <td>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling,</td>		Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling,
India. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Ingestion: There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC1373) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual: animal experiments indicate that ingestion of less than 40 gram may be fatal. Skin contact: There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis condition Skin contact: Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Skin contact: Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin		may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove
Insection These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Ingestion: There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual: animal experiments indicate that ingestion of less than 40 gram may be fatal. Skin contact: There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis condition Skin contact: Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Skin contact: Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external dam		The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression.
light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest.Ingestion:There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal.Skin contact:There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dematitis conditionSkin contact:Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a d		These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include
arowsiness, inrging in the ears, biurred or double vision, vomiting and sensitions of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Ingestion: There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. [ICSC13733] Ingestion: The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal. There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis condition Skin contact: Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Skin contact: Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact: Skin contact with the material may be harmful; systemic effects may result following direct contact or after a delay of some		light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness,
Institution in the initial institution in the initial institution in the initial institution in the initial initinitial initinitial initial initial initial initial ini		drowsiness, ringing in the ears, biurred or double vision, vomiting and sensations of neat, cold or numbress twitching tremors
Ingestion:There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal.Insertion:There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dematitis conditionSkin contact:Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dematitis which is characterised by		convulsions, unconsciousness, depression of breathing, and arrest.
Ingestion:irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal.There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis conditionSkin contact:Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		There is strong evidence to suggest that this material can cause, if swallowed once, very serious,
Ingestion:Insk of chemical pneumonitis; senous consequences may result. (ICSC 13733) The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal.InstructThere is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		irreversible damage of organs. Swallowing of the liquid may cause aspiration into the lungs with the
Ingestion:International not Nor Deen classified by DC Directives of other classified information systems as individually ingestion. This is because of the lack of corroborating animal or human evidence. Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal.InsertionThere is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis conditionSkin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		Tisk of chemical pneumonifis; serious consequences may result. (ICSC13/33)
Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal. There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Skin contact: Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by	Ingestion:	ingestion". This is because of the lack of corroborating animal or human evidence.
animal experiments indicate that ingestion of less than 40 gram may be fatal.There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis conditionSkin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		Accidental ingestion of the material may be seriously damaging to the health of the individual;
than 40 gram may be tatal.There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		animal experiments indicate that ingestion of less
Skin contact: Skin contact: Skin contact: Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		than 40 gram may be tatal.
 Skin contact: Skin con		serious, irreversible damage of organs. The material may accentuate any pre-existing dermatitis
Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		condition
Skin contact:material may still produce health damage following entry through wounds, lesions or abrasions. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		Skin contact is not thought to have harmful health effects (as classified under EC Directives); the
Skin contact: Skin contact: Skin contact: Skin contact: Copen curs, abraded of initiated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by	Skin contact:	material may still produce health damage following entry through wounds, lesions or abrasions.
injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		Entry into the blood-stream, through, for example, cuts, abrasians or lesions, may produce systemic.
external damage is suitably protected. Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		injury with harmful effects. Examine the skin prior to the use of the material and ensure that any
Skin contact with the material may be harmful; systemic effects may result following absorption. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		external damage is suitably protected.
Ine material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by		Skin contact with the material may be harmful; systemic effects may result following absorption.
		Ine material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by
redness, swelling and blistering.		I aciay of some time, repeated exposure can cause contract definations which is chalacterised by

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	12 of 19



Eye:	There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain. The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated.
Chronic:	There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Persons with a history of asthma or other respiratory problems or are known to be sensitised, should not be engaged in any work involving the handling of isocyanates. The chemistry of reaction of isocyanates, as evidenced by MDI, in biological milieu is such that in the event of a true exposure of small MDI doses to the mouth, reactions will commence at once with biological macromolecules in the buccal region and will continue along the digestive tract prior to reaching the stomach. Reaction products will be a variety of polyureas and macromolecular conjugates with for example mucus, proteins and cell components. Women exposed to xylene in the first 3 months of pregnancy showed a slightly increased risk of miscarriage and birth defects. Evaluation of workers chronically exposed to xylene has demonstrated lack of genetic toxicity. Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS]

Euroroof Spray SA Primer:

Toxicity	Irritation
Not available	Not available

Xylene:	
Toxicity	Irritation
Dermal (rabbit) LD50: >1700 mg/kg ^[2]	Eye (human): 200 ppm irritant
Inhalation(Rat) LC50; 5922 ppm4h ^[1]	Eye (rabbit): 5 mg/24h SEVERE
Oral(Mouse) LD50; 2119 mg/kg ^[2]	Eye (rabbit): 87 mg mild
	Eye: adverse effect observed (irritating) ^[1]
	Skin (rabbit):500 mg/24h moderate

Polymeric Diphenylmethane Diisocyanate:

Toxicity	Irritation
Dermal (rabbit) LD50: >9400 mg/kg[2]	Eye (rabbit): 100 mg - mild
Inhalation(Rat) LC50; 0.49 mg/L4h ^[2]	
Oral(Rat) LD50; 43000 mg/kg ^[2]	

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity; 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances.

	Reproductive effector in rats
	The material may produce severe irritation to the eye causing pronounced inflammation.
Vulana	Repeated or prolonged exposure to irritants may produce conjunctivitis.
Xylene:	The material may cause skin irritation after prolonged or repeated exposure and may
	produce on contact skin redness, swelling, the production of
	vesicles, scaling and thickening of the skin.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	13 of 19



Polymeric Diphenylmethane Diisocyanate:	product The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Aromatic and aliphatic diisocyanates may cause airway toxicity and skin sensitization. Monomers and prepolymers exhibit similar respiratory effect. Of the several members of diisocyanates tested on experimental animals by inhalation and oral exposure, some caused cancer while others produced a harmless outcome.
Euroroof PU Primer / Sealer & Polymeric Diphenylmethane Diisocyanate:	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than others, and exposure to other irritants may aggravate symptoms. Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema. Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure. The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated [I lymphocytes] immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. Isocyanate vapours are irritating to the airways and can cause their inflammation, with wheezing, gasping, severe distress, even loss of consciousness and fluid in the lungs. Nervous system symptoms that may occur include headache, sleep disturbance, euphoria, inco-ordination, anxiety, depression and paranoia.
Xylene & Polymeric	The substance is classified by IARC as Group 3:
Diphenyimetriane Diisocyanate:	Evidence of carcinogenicity may be inadequate or limited in animal testing.

Acute Toxicity	•	Carcinogenicity	• • • • • • • • • • • • • • • • • • •	
Skin Irritation/Corrosion	~	Reproductivity	×	
Serious Eye Damage/Irritation	~	STOT - Single Exposure		
Respiratory or Skin Sensitisation	 Image: A second s	STOT - Repeated Exposure	 	
Mutagenicity	×	Aspiration Hazard	×	

Legend:

× - Data either not available or does not fill the criteria for classification.

✓ - Data available to make classification.

11.2.1 Endocrine Disruption Properties

Not available.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Euroroof Spray SA Primer:

End point	Test duration (Hr)	Species	Value	Source
Not available	Not available	Not available	Not available	Not available

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	14 of 19



Methylene Chloride:

End point	Test duration (Hr)	Species	Value	Source
NOEC (ECx)	24h	Algae or other aquatic plants	0.98mg/l	4
BCF	1008h	Fish	2-5.4	7
EC50	72h	Algae or other aquatic plants	202-286mg/l	4
LC50	96h	Fish	2-3.3mg/l	4
EC50	48h	Crustacea	150-218mg/l	4
EC50	96h	Algae or other aquatic plants	0.98mg/l	4

LPG (Liquefied Petroleum Gas):

End point	Test duration (Hr)	Species	Value	Source
EC50(ECx)	96h	Algae or other aquatic plants	7.71mg/l	2
LC50	96h	Fish	24.11mg/l	2
EC50	96h	Algae or other aquatic plants	7.71mg/l	2

Dimethyl Ether:

End point	Test duration (Hr)	Species	Value	Source
EC50	48h	Crustacea	>4400mg/L	2
LC50	96h	Fish	1783.04mg/l	2
NOEC (ECx)	48h	Crustacea	>4000mg/l	1
EC50	96h	Algae or other aquatic plants	154.917mg/l	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites. For Aromatic Substances Series:

Environmental Fate: Large, molecularly complex polycyclic aromatic hydrocarbons, or PAHs, are persistent in the environment longer than smaller PAHs.

Atmospheric Fate: PAHs are 'semi-volatile substances'' which can move between the atmosphere and the Earth's surface in repeated, temperature-driven cycles of deposition and volatilization. Terrestrial Fate: BTEX compounds have the potential to move through soil and contaminate ground water, and their vapors are highly flammable and explosive.

For Polyisocyanates:

Polyisocyanates are not readily biodegradable. However, due to other elimination mechanisms (hydrolysis, adsorption), long retention times in water are not to be expected. The resulting polyurea is more or less inert and, due to its molecular size, not bioavailable.

For Isocyanate Monomers:

Environmental Fate: Isocyanates, (di- and polyfunctional isocyanates), are commonly used to make various polymers, such as polyurethanes. Polyurethanes find significant application in the manufacture of rigid and flexible foams. They are also used in the production of adhesives, elastomers, and coatings.

For Xylenes:

log Koc : 2.05-3.08; Koc : 25.4-204; Half-life (hr) air : 0.24-42; Half-life (hr) H2O surface water : 24-672; Half-life (hr) H2O ground : 336-8640; Half-life (hr) soil : 52-672; Henry's Pa m3

/mol : 637-879; Henry's atm m3 /mol - 7.68E-03; BOD 5 if unstated - 1.4,1%; COD - 2.56,13% ThOD - 3.125 : BCF : 23; log BCF : 1.17-2.41.

Environmental Fate: Most xylenes released to the environment will occur in the atmosphere and volatilisation is the dominant environmental fate process. Soil - Xylenes are expected to have moderate mobility in soil evaporating rapidly from soil surfaces.

DO NOT discharge into sewer or waterways.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	15 of 19



12.2 Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)

12.3 Bioaccumulation potential

Ingredient	Bioaccumulation
Xylene	MEDIUM (BCF = 740)

12.4 Mobility in soil

No data available for all ingredients.

12.5 Results of PBT and vPvB assessment

	P	В	T	
Relevant available data	Not available	Not available	Not available	
PBT	×	×	×	
vPvB	×	×	×	
PBT Criteria fulfilled?			No	
vPvB			No	

12.6 Endocrine Disruption Properties

Not available.

12.7. Other adverse effects

Not available.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal Considerations:	Disposal of this product and its packaging must comply with all applicable environmental protection and waste disposal legislation, including any requirements set by local authorities. Any unwanted or non-recyclable material should be disposed of through a licensed waste disposal contractor. Transportation of such waste may be subject to ADR (International Carriage of Dangerous Goods by Road) regulations and must be managed in accordance with those requirements.
Waste code:	080111* waste paint and varnish containing organic solvents or other hazardous substances.
Special precautions:	This material and its container must be disposed of in a safe way. Caution should be exercised when handling empty containers that have not been properly cleaned or rinsed, as they may retain hazardous residues. Spillage and wash water from cleaning tools must be prevented from entering soil, watercourses, drains, or sewer systems. Empty containers should be directed to authorised waste disposal or appropriate local recycling facilities.
Further information available via:	https://www.alumascroofing.com/downloads/disposal-guides/

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	16 of 19



14. TRANSPORT INFORMATION

Labels required:



3Y.

Marine Pollutant:

Hazchem:

Land transport (ADR):

14.1 UN number	1993	
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.	
	Class:	3
14.3 Indrispon nazara class(es)	Subrisk:	N/A
14.4 Packing group		
14.5 Environmental hazard	Not applicable	
	Hazard identification (Kemler):	30
	Classification code:	F1
14.6 Spacial procedutions for user	Hazard label:	3
14.6 special precautions for user	Special provisions:	274 601
	Limited quantity:	5L
	Tunnel restriction code:	2 (D/E)

Air transport (ICAO-IATA/DGR):

14.1 UN number	1993	
14.2 UN proper shipping name	Flammable liquid, n.o.s. *	
14.3 Transport hazard class(es)	ICAO/IATA class:	3
	ICAO/IATA subrisk:	N/A
	ERG code:	3L
14.4 Packing group		
14.5 Environmental hazard	Not applicable	
14.6 Special precautions for user	Special provisions:	A3
	Cargo only packing instruction:	366
	Cargo only maximum qty/pack:	220L
	Passenger and cargo packing instruction:	355
	Passenger and cargo maximum qty/pack:	60 L
	Passenger and cargo limited aty packing instructions:	Y344
	Passenger and cargo limited maximum qty/pack:	10 L

Sea transport (IMDG-Code/GGVSee):

14.1 UN number	1993	
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.	
14.3 Transport hazard class(es)	IMDG class:	3
	IMDG subrisk:	Not applicable
14.4 Packing group		
14.5 Environmental hazard	Not applicable	
14.6 Special precautions for user	EMS number:	F-E , S-E F-D , S-U
	Special provisions:	223 274 955
	Limited quantities:	5 L

Inland waterways transport (ADN):

14.1 UN number	1993	
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.	
14.3 Transport hazard class(es)	Class:	3
	Subrisk:	N/A
14.4 Packing group		
14.5 Environmental hazard	Environmentally hazardous	
14.6 Special precautions for user	Classification code:	F1
	Special provisions:	274; 601
	Limited quantity:	5 L
	Equipment required:	PP, EX, A
	Fire cones numbers:	0

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	17 of 19



14.7. Transport in bulk according to Annex II of MARPOL and the IBC code

Not applicable.

14.8. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product Name	Group	
xylene	Not available	
polymeric diphenylmethane diisocyanate	Not available	

14.9. Transport in bulk in accordance with the ICG Code

Product Name	Ship Type
xylene	Not available
polymeric diphenylmethane diisocyanate	Not available

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Xylene is found on the following regulatory lists:

EU Consolidated List of Indicative Occupational Exposure	European Union - European Inventory of Existing
Limit Values (IOELVs)	Commercial Chemical Substances (EINECS)
EU European Chemicals Agency (ECHA) Community Rolling	European Union (EU) Regulation (EC) No 1272/2008 on
Action Plan (CoRAP) List of Substances	Classification, Labelling and Packaging of Substances and
	Mixtures - Annex VI
EU REACH Regulation (EC) No 1907/2006 - Annex XVII -	International Agency for Research on Cancer (IARC) -
Restrictions on the manufacture, placing on the market and	Agents Classified by the IARC Monographs

Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles Europe EC Inventory

Polymeric Diphenylmethane Diisocyanate is found on the following regulatory lists:

EU REACH Regulation (EC) No 1907/2006 - Annex XVII -Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

ECHA summary:					
Ingredient	CAS number	Index No	ECHA Dossier		
Xylene	1330-20-7	601-022-00-9	01-2119488216-3	2-XXXX	
Harmonisation (C&L Inventory)	Hazard Class and C	ategory Code(s)		Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Flam. Liq. 3; Acut	e Tox. 4; Skin Irrit. 2; A	Acute Tox. 4	GHS02; GHS07; Wng	H226; H312; H315; H332
2	Acute Tox. 4; Skin II 2; Resp. STOT SE 3; Repr. 1B; STOT SE 1 Lact.; Aquatic Acu	rit. 2; Acute Tox. 4; A Narc. STOT SE 3; Aq STOT RE 1; Flam. Lic te 1; Asp. Tox. 2	Asp. Tox. 1; Eye Irrit. uatic Chronic 2; q. 2; Acute Tox. 4;	GHS02; GHS07; Wng; GHS08; Dgr; GHS01; GHS09	H312; H315; H332; H304; H335; H336; H411; H360; H370; H372; H225; H302; H318; H362; H400
Harmonisation Code 1	= The most prevalen	t classification. Harm	onisation Code 2 = Th	ne most severe (classification.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	18 of 19



Ingredient	CAS number	Index No	ECHA Dossier
Polymeric Diphenylmethane Diisocyanate	9016-87-9	Not available	01-2119457024-46-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Skin Irrit. 2; Eye Irrit. 2; Acute Tox. 2; Resp. Sens. 1; Resp. STOT SE 3; STOT RE 2; Skin Sens. 1; Carc. 2	GHS08; GHS06; Dgr; GHS07; Wng	H315; H319; H330; H334; H335; H373; H317; H351
2	Eye Irrit. 2; Resp. Sens. 1; Resp. STOT SE 3; STOT RE 2; Skin Sens. 1; Carc. 2; Acute Tox. 4; Acute Tox. 4; Skin Corr. 1B; Aquatic Chronic 1; Acute Tox. 1; Muta. 2	GHS08; GHS06; Dgr; GHS07; Wng; GHS05; GHS09	H319; H334; H335; H373; H317; H351; H302; H312; H314; H330; H341; H410
Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.			

National Inventory	Status
Australia - AIIC / Australia Non- Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (xylene; polymeric diphenylmethane diisocyanate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (polymeric diphenylmethane diisocyanate)
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZloC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory. No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets).

16. OTHER INFORMATION

Full text risk and hazard codes:

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360 May damage fertility or the unborn child.
- H362 May cause harm to breast-fed children.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Reference No:	SDS-AP006	Version:	2.1
Date of issue:	27/05/2025	Page:	19 of 19



SDS version summary:

Version	Date of Update	Section Updated
2.0	24/01/2023	Template Change
2.1	27/05/2025	Section 13 update

Other information:

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

- EN 166 Personal eye-protection
- EN 340 Protective clothing

EN 374 Protective gloves against chemicals and micro-organisms

EN 13832 Footwear protecting against chemicals

EN 133 Respiratory protective devices

Definitions and abbreviations:

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit. IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard **OSF:** Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIOC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory. INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

The contents and format of this SDS are in accordance with EEC Commission Directive 1999/45/EC, 67/548/EC, 1272/2008/EC and EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.