Reference No:SDS-HYD003Date of issue:01/07/2021



1. IDENTIFICATION OF THE SUBSTRATE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name/designation: Flex-Flash F.

1.2 Use of substance/preparation

Reinforcement for hot applied bituminous liquid membranes.

1.3 Manufacturer/Supplier

Supplier: Alumasc Building Products Ltd White House Works, Bold Road, Sutton, St Helens, Merseyside, United Kingdom, WA9 4JG Tel: +44 (0)1744 648400 e-mail: <u>technical@alumascroofing.com</u>

1.4 Manufacturer/Supplier

Emergency telephone: 01744 648 400 - (Mon-Thurs – 08.30-17.00 Fri – 08.30-16.00)

2. HAZARDS IDENTIFICATION

Substances which could entail a danger	%	CAS No.	Symbols	R
None				
Impurities which could entail a danger				
None				

Other:

Polyethyleneterephthalate synthetic fibres (CAS 25038-59-9) 98-99%. Titanium dioxide (CAS 13463-67-7).

3. COMPOSITION AND INFORMATION ABOUT THE COMPONENTS

Classification according to Directive 67/548/EEC:

Classification according to Dire	ective o//546/EEC:
Explosive:	Not applicable.
Oxidizing:	Not applicable.
Very highly flammable:	Not applicable.
Highly flammable:	Not applicable.
Flammable:	Not applicable.
Mutagenic:	Not applicable.
Highly poisonous:	Not applicable.
Poisonous:	Not applicable.
Harmful:	Not applicable.
Corrosive:	Not applicable.
Irritating:	Not applicable.
Carcinogenic:	Not applicable.
Others (to specify):	Not applicable.

4. FIRST AID MEASURES

4.1 Skin

Consult a doctor if any symptoms persist.

4.2 Eyes

Consult a doctor if any symptoms persist.

4.3 Ingestion

Do not induce vomiting; take to hospital with a copy of this safety data sheet.

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

FLEX-FLASH F SAFETY DATA SHEET

Reference No:SDS-HYD003Date of issue:01/07/2021



4.4 Inhalation

Remove to fresh air. Consult doctor if any symptoms persist.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing agents

Use extinguisher suitable for the cause of the fire – Foam, Dry Powder, Water.

5.2 Unsuitable extinguishing agents

None.

6. ACCIDENTIAL RELEASE MEASURES

Not applicable.

7. HANDLING AND STORAGE

7.1 Handling

Special handling precautions: None.

7.2 Storage

Special storage precautions: None.

Packing materials to avoid: None

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure controls

If significant amounts of dust are generated during handling reduce exposures using good general ventilation, or local exhaust ventilation under extreme conditions.

8.2 Personal protective equipment

Use an approved dust respirator if the dust levels generated using the handling of this product may exceed 10 mg/m³. Under such extreme conditions use eye protection to prevent dust entering the eye.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 General information

Supplied in roll form with no odour. White in colour.

9.2 Important health, safety and environmental information

Melting point: Softening point (preparation): Boiling point: Decomposition points	250-260°C. Not applicable. Not applicable.
with decomposition products:	Not applicable.
pH:	Not applicable.
Vapour pressure at 20°C:	Not applicable.
Relative density at 20°C:	Not known.
Kinematic viscosity at 40°C:	Not known.

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

Alumasc Roofing is a trading name of Alumasc Building Products Ltd Registered in England & Wales No: 2992960

FLEX-FLASH F SAFETY DATA SHEET

Reference No:SDS-HYD003Date of issue:01/07/2021



Physical state at 20°C:Solid. AverageSolubility in water at 20°C:Insoluble.Flash point:Not applicable.Autoignition:515°C.Surface tension:Not applicable.Distribution coefficient/n octanol/water:Not applicable.Colour:White fibres in m

Solid. Average fibre dimensions = 19 microns diameter. Insoluble. Not applicable. 515°C. Not applicable. Not applicable. White fibres in melt spun fleece form.

10. STABILITY AND REACTIVITY

10.1 Stability

Oxides of carbon may be produced in a fire situation.

10.2 Materials to be avoided

Avoid contact with oxidising agents, acids and alkalis.

11. TOXOCOLOGICAL INFORMATION

Inhalation of excessive amounts of dust may cause temporary upper respiratory tract irritation. Skin or eye contact may cause temporary minor irritation.

12. ECOLOGICAL INFORMATION

No information is available on this product. Polyester is stable and does not decompose under normal soil conditions.

Class EN of waste: 20 01 39.

Recycle product if possible.

14. TRANSPORT INFORMATION

13. DISPOAL CONSIDERATIONS

Not classified as hazardous for the purposes of transport by road, rail, sea or air.

15. REGULATORY INFORMATION

Not classified as hazardous.

16. OTHER INFORMATION

No other information.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.