

1. IDENTIFICATION OF THE SUBSTRATE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name/designation: Eurorooft Alpha.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Main use category: Industrial & professional uses.

1.3 Manufacturer/Supplier

Supplier:
Alumasc Building Products Ltd
White House Works, Bold Road, Sutton, St Helens, Merseyside, United Kingdom, WA9 4JG
Tel: +44 (0)1744 648400
e-mail: technical@alumascroofing.com

1.4 Manufacturer/Supplier

Emergency telephone: 01744 648 400 - (Mon-Thurs – 08.30-17.00 Fri – 08.30-16.00)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008:

Flam. Liq. 3: H226; Acute Tox. 4: H312, H332; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 3: H412.

Flammable liquid and vapour. Harmful in contact with skin and if inhaled. Causes skin irritation. May cause allergic skin reaction.

Harmful to aquatic organisms with long lasting effects.

2.2 Labelling according to Regulation (EU) 1272/2008

Hazard pictures:



GHS02



GHS07

Signal word:

Warning.

Hazard statements:

H226: Flammable liquid and vapour.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H31+H332: Harmful in contact with skin and if inhaled.
H412: Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210: Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P260: Do not breathe vapours.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P501: Dispose of contents/container according to local regulations.

Additional labelling:

215-535-7 Xylene.
411-700-4 1,6-Hexadiyl-Bis[2-[2-(1-Ethylpentyl)-3-Oxazolidinyl]- -Ethyl]-Carbamate.
500-125-5 Isophorone Diisocyanate Homopolymer.

2.3 Other hazards

This product is not identified as a PBT or vPBT substance.

3. COMPOSITION AND INFORMATION ABOUT THE COMPONENTS

3.1 Substance

Low odour polyurethane liquid base coating.

3.2 Mixture

Ingredient	Concentration %	Cas No.	Ec No.	Clp Classification
Xylene (Mixed Isomers)	10-13	1330-20-7	215-535-7	Flam. Liq. 3: H226; Acute. Tox. 4: H312; Acute Tox. 4: H332; Skin Irrit. 2: H315;
Diphenyl Cresyl Phosphate	3-8%	-	945-730-9	Aquatic Acute 1: H400; Aquatic Chronic 3: H412
1,6-Hexadiyl-Bis[2-[2-(1-Ethylpentyl)-3-Oxazolidinyl]-Ethyl]-Carbamate	1-5	140921-24-0	411-700-4	Skin Sens. 1: H317
Isophorone Diisocyanate Homopolymer	1-2.5	53880-05-0	500-125-5	Skin Sens. 1: H317; STOT SE 3 H335
Diuron (ISO)	>0.1 - <0.25	330-54-1	206-354-4	Acute Tox. 4: H302; STOT RE 2: H373; Carc. 2 H351; Acute 1: H400; Aquatic Chronic 1: H410

4. DESCRIPTION OF FIRST AID MEASURES

4.1 Description of first aid measures

General advice:	If possible, remove affected person from source of contamination. Symptoms of poisoning may even occur after several hours; therefore, medical observation for at least 48 hours after the accident.
Inhalation:	Provide fresh air in a comfortable upright sitting position. Get medical attention if any discomfort continues. If breathing is difficult oxygen may be administered by properly trained personnel. Perform artificial respiration if breathing has stopped.
Skin contact:	Remove contaminated clothing unless stuck to skin and wash skin with copious amounts of soap and water. Get medical attention if discomfort continues.
Eye contact:	Check/remove any contact lenses from the eyes before rinsing. Wash eyes with plenty of water for at least 15 minutes and get medical attention if symptoms persist.
Ingestion:	Do not induce vomiting. Loosen tight clothing, rinse mouth and provide fresh air. Seek medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

Not expected to present a significant hazard under anticipated conditions of normal use.

4.3 Indication of any immediate medical attention and special treatment needed

Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media:

CO₂, foam, dry powder. Use extinguishing media for the appropriate situation.

Unsuitable extinguishing media:

Water, high volume water jet.

5.2 Special hazards arising from the substance or mixture

Due to excessive heat/pressure build up closed containers can burst when heated. May ignite at high temperature. When heated to decomposition, may release vapours/gases that may be hazardous: Carbon Dioxide, Carbon Monoxide, Nitrous Oxides and Phosphorus Oxides.

5.3 Advice for fire-fighters

Remove containers away from fire and water cool.

Use appropriate protective clothing and an approved respirator during firefighting.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

When cleaning a spillage outside normal working area, wear suitable protective clothing such as nitrile gloves and suitable goggles. Avoid contact with skin and eyes. Provide adequate ventilation. In an unventilated or tightly confined space respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit. (WEL).

6.2 Environmental precautions

Do not allow product to enter drains.

In case of any contamination of watercourses, contact relevant authorities.

6.3 Methods and materials for containment and cleaning up

In the first instance make efforts to contain the spilled material. Collect spillage using an inert absorbent material, place in containers suitable for disposal, seal securely and deliver for disposal in accordance with local regulations.

6.4 Reference to other sections

Personal protection covered in Section 8.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Always observe good industrial hygiene practices. Avoid contact with skin, eyes and clothing. Avoid breathing vapours and spray mists. Under normal working conditions, respiratory protection should not be necessary. However, in confined spaces without adequate ventilation, a suitable filter mask may be required. When using, do not consume food, drink or smoke. Remove contaminated clothing.

7.2 Conditions for safe storage, including any incompatibilities

Store in the tightly closed original container in a dry place. Protect from frost and direct sunlight. Store at temperature between 5 - 25°C.

7.3 Specific end use(s)

No specific data available.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Workplace Exposure Limits (WEL) GB EH40:

Ingredient		Time Weighted Average (Twa) 8 Hours				Short Term Exposure Limit (Stel) 15 Mins			
Xylene (mixed Isomers)		50ppm (Sk)/220mg per m3 (Sk)				100ppm (Sk)/441mg/m3 (Sk)			
For Xylene:									
Derived No Effect Level (DNEL)									
Workers					Consumers				
Route of exposure	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effects local	Acute effects systemic	Chronic effects local	Chronic effects systemic	
Oral	Not required				Not applicable				
Inhalation	289 mg/m3	289 mg/m3	N/A	77 mg/m3	174 mg/m3	174 mg/m3	N/A	14.8 mg/m3	
Dermal	Not applicable				180 mg/kg	Not applicable			108 mg/kg
Predicted No Effect Concentration (PNEC)									
Fresh water					0.327 mg/l				
Marine water					0.327 mg/l				
Intermittent releases					0.327 mg/l				
Sewage treatment plant (STP)					6.58 mg/l				
Fresh water sediment					12.46 mg/kg dry weight (d.w.)				
Marine sediment					12.46 mg/kg dry weight (d.w.)				
Soil					2.31 mg/kg dry weight (d.w.)				

8.2 Exposure controls

Appropriate engineering controls:

In enclosed areas use local exhaust ventilation, or similar engineering controls to ensure vapours remain below occupational exposure limits.

Personal protective equipment:

Eye protection:	Wear safety glasses with side-shields.
Skin protection:	Wear suitable gloves. The glove material has to be impermeable and resistant to the product. Test the durability of the gloves before use. Protective gloves should be replaced at first signs of wear. Protective clothing to include safety shoes, long-sleeved working clothing, long trousers).
Respiratory protection:	Under normal working conditions, respiratory protection should not be necessary. However, in confined spaces, where there is a risk of pollution above the WEL limit, a suitable filter mask may be required.

Environmental exposure controls:

Do not allow product to enter drains. In case of any contamination of watercourses, contact relevant authorities. See also measures detailed in Sections 6 & 7.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance:	Pigmented thixotropic liquid.
Odour:	Solvent – Aromatic.
Odour threshold:	No data available.
Ph:	No data available.
Melting point/freezing point:	No data available.
Boiling point/range:	>130 (°C).

Flash point:	34 (°C) (closed cup).
Evaporation rate:	No data available.
Flammability:	No data available.
Upper explosion limit:	10.8% (V).
Lower explosion limit:	1% (V).
Vapour density (air = 1):	>1.
Relative density:	~1.49.
Solubility in H2O:	Insoluble and immiscible.
Partition co-efficient:	No data available.
Auto-ignition temperature:	>430 (°C).
Decomposition temperature:	No data available.
Viscosity:	>5000mPas.
Explosive properties:	No data available.
Oxidising properties:	No data available.

9.2 Other information

No data available.

10. STABILITY AND REACTIVITY

10.1 Reactivity

No hazardous reactions under normal conditions of use.

10.2 Chemical stability

This product is extremely stable under normal temperature conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions under normal conditions of use.

10.4 Conditions to avoid

Avoid extreme excessive heat for prolonged periods of time. Avoid contact with water, as the product will naturally harden into a hard mass in contact with water and moisture.

10.5 Materials to avoid

Alcohols, strong acids, strong oxidising materials.

10.6 Hazardous decomposition products

No dangerous decomposition products when stored and handled correctly.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity: Harmful if inhaled. Harmful in contact with skin.

Xylene				
Route	Species	Method	Result	ATEi
ORL	MUS	LD50	5251 mg/kg	-
DRM	RBT	LD50	>4200 mg/kg	1100
INH	RAT	LC50	29091 mg/l/4h	11

Skin corrosion/Irritation:	Causes skin irritation.
Serious eye damage/irritation:	Not classified based on available information.
Respiratory sensitisation:	Not classified based on available information.
Skin sensitisation:	May cause allergic skin reaction.

Germ cell mutagenicity: Not classified based on available information.
Carcinogenicity: Not classified based on available information.
Reproductive toxicity: Not classified based on available information.
STOT-single exposure: Not classified based on available information.
STOT-repeated exposure: Not classified based on available information.
Aspiration hazard: Not classified based on available information.

12. ECOLOGICAL INFORMATION

12.1 Ecological information

Diphenyl Cresyl Phosphate:

Test	Result	Species	Exposure
OECD 209 Activated Sludge, Respiration Inhibition Test	Acute EC50 >10000 mg/l	Bacteria	3 hours
-	Acute EC50 10 mg/l	Fish - Daniorerio	96 hours
OECD 201 Alga, Growth Inhibition Test	Chronic IC50 0,99 mg/l	Algae - Selenastrum capricornutum	72 hours

For Diuron (ISO):

Test	Result	Species	Exposure
OECD 203 Fish, Acute Toxicity Test	Acute LC50 14,7 mg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours
OECD 202 Daphnia sp. Acute Immobilization Test	Acute EC50 1,4 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
OECD 201 Alga, Growth Inhibition Test	Acute EC50 0,022 mg/l Fresh water	Algae - Scenedesmus subspicatus	72 hours
OECD 209 Activated Sludge, Respiration Inhibition Test	Acute EC50 3080 mg/l	Bacteria - Activated sludge	0.5 hours
OECD 204 Fish, Prolonged Toxicity Test: 14-Day Study	Chronic NOEC 0,41 mg/l Fresh water	Fish - Oncorhynchus mykiss	28 days
OECD 211 Daphnia Magna Reproduction	Chronic NOEC 0,56 mg/l Fresh water	Daphnia - Daphnia magna	21 days
OECD 201 Alga, Growth Inhibition Test, Growth	Chronic NOEC 0,0032 mg/l Fresh water	Algae - Scenedesmus subspicatus	71 hours

12.2 Persistence & degradability

Diphenyl Cresyl Phosphate:

Aquatic Half-Life	Photolysis	Biodegradability
-	-	Readily
Rate of Degradation /Elimination (%)	PERIOD	TEST
84%	28 days	OECD 301B Ready Biodegradability – CO2 Evolution Test
75%	28 days	OECD 301C Ready Biodegradability – Modified MITI Test (I)

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

This mixture contains no PBT or vPvB components at levels of 0.1% or higher.

12.6 Other adverse effects

No data available.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

All material residues and packaging must be disposed of in accordance with local/national waste disposal regulations and environmental controls.

Cured product is considered inert.

Packaging containing liquid product will meet the criteria for hazardous waste. Code: 15 01 10*

14. TRANSPORT INFORMATION

	ADR/IATA	IMDG
14.1 UN number	Not subject	
14.2 Proper shipping name		
14.3 Transport hazard class(es)/marks		
14.4 Packing group/Labels		
14.5 Environmental hazards	No	
14.6 Special precautions for user		
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code"		

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibition/Restriction	
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII):	Not applicable.
REACH - Candidate list of substances of very high concern for authorisation (Article 59):	None of the components are listed.
REACH - List of substances subject to authorisation (Annex XIV):	Not applicable.
REACH information:	All substances contained in this product are pre-registered or registered by our upstream suppliers and/or excluded from the regulation and/or exempted from the registration.

15.2 Chemical safety assessment

This product contains substances for which Chemical Safety Assessments are still required.

16. OTHER INFORMATION

Hazard Statements for components in section 3:

H226:	Flammable liquid and vapour.
H312:	Harmful in contact with skin.
H315:	Causes skin irritation.
H317:	May cause an allergic skin reaction.
H332:	Harmful if inhaled.
H335:	May cause respiratory irritation.
H351:	Suspected of causing cancer.
H373:	May cause damage to organs through prolonged or repeated exposure.
H400:	Very toxic to aquatic life.
H410:	Harmful to aquatic life with long lasting effects.
H412:	Harmful to aquatic life with long lasting effects.

Sectors of use/relevant identified uses of the mixture:

SU3:	Industrial uses: Uses of substances as such or in preparations at industrial sites.
SU19:	Building and construction work.
SU22:	Professional uses: Public domain (administration, education, entertainment, services, craftsmen).

Uses advised against:

SU21:	Consumer uses: Private households / general public / consumers.
-------	---

Wording of the hazard classes:

Acute Tox:	Acute Toxicity.
Flam. Liq:	Flammable Liquids.
Skin Irrit:	Skin Irritation.
Skin Sens:	Skin Sensitisation.
STOT SE:	Specific Target Organ Toxicity - Single Exposure.
ADR:	The European Agreement on the International Transport of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service.
DNEL:	Derived No Effect Level.
GHS:	Globally Harmonized System.
IATA:	International Air Transport Association.
IMDG:	International Maritime Code for Dangerous Goods.
LC50:	Median Lethal Concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period).
LD50:	Median Lethal Dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals).
MARPOL:	International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978.
PBT:	Persistent, Bioaccumulative and Toxic.
PNEC:	Predicted No Effect Concentration.
REACH:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency.
SVHC:	Substances of Very High Concern.
VOC:	Volatile Organic Compounds.
vPvB:	Very Persistent and very Bioaccumulative.
WEL:	Workplace Exposure Limit.

Training:

This material should only be used by trained personnel.

All the information supplied on this data sheet applies only when the product is used for the prescribed application and in accordance with the directions for use.

Please make this data available to all persons involved with the production, transportation and use of this product.

CALTECH ALPHA
SAFETY DATA SHEET

Reference No: SDS-CAL012
Date of issue: 01/07/2021



The contents and format of this SDS are in accordance with EEC Commission Directive 1999/45/EC, 67/548/EC, 1272/2008/EC and EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.



Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

AlumasC Roofing is a trading name of AlumasC Building Products Ltd
Registered in England & Wales No: 2992960

www.alumascroofing.com