

Product Datasheet

BluRoof 225FF Filter Sheet

Sheet No: PD912FR
Issued: July 2021
Pages: 1 of 1

Description

BluRoof 225FF Filter Sheet is a needle punched, non-woven, polypropylene geotextile filter fabric.

Use

For use as a filter fabric enclosing Alumasc BluRoof void former water storage modules to prevent the passage of fines.

Features

- UV resistant.
- Contains no chemical binders.

Size	4.85m x 100m 4.85m x 200m
Thickness	3mm nominal
Tensile Strength (BSEN 10319)	3kN/m ² machine direction 9kN/m ² transverse direction
Extension (BSEN 1996)	136% machine direction 69% transverse direction
Flow rate (BS 6906 pt 3 1989)	314.85 litres/m ² /second
Weight	220g/m ²

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.