

Product Datasheet

Hydrotech Monomelt Reinforcing Mesh

Sheet No: PD223FR
Issued: July 2021
Pages: 1 of 1

Description

Hydrotech Monomelt Reinforcing Mesh is a resin coated glass fibre mesh of 10mm x 10mm square dimension, white in colour.

Use

For use as a continuous reinforcement in Hydrotech Monomelt 6125 applications, where minimal or no expansion or movement is anticipated.

Application

Fully embedded into the first layer of Hydrotech Monomelt 6125, with butt jointed edges, prior to application of the overlying protection sheet.

Storage

Store upright in a clean, dry location, away from heat sources.

Product Data

Thickness	0.75mm
Width	1000mm
Length	50m
Weight	110g/m ²
Weight per roll	5.5kg
Mesh size	10mm x 10mm

Performance Data

Tensile Strength – warp	1900N/50mm
Tensile Strength – weft	1600N/50mm
Maximum elongation – warp	3.5%
Maximum elongation – weft	4.0%

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.