

Product Data Sheet

Caltech QC SP Primer

Sheet No: PDFR705
Issued: July 2021
Pages: 1 of 1

Description

Caltech QC Primer SP is a single component, cold applied, fast curing primer for the priming of existing single plymembranes.

Application

Surface is to be dry, clean, and free from all contaminants.

Where applicable, scrub all contaminated surfaces with soapy water and rinse down with clean water. Apply one coat of Caltech SP Primer at an approximate coverage rate of 0.06 l/m², by brush or short pile roller.

Product Data

Packaging	0.5l drum
Colour(s)	Yellowish
Coverage	0.06 l/m ² minimum.
Application	Brush or short pile roller
Cure time	Rainproof: approximately 20 minutes at +20°C
Storage	Can be stored unopened in a cool, dry, well ventilated place above freezing and out of direct sunlight in the original container. If the contents have been opened, re-seal ensuring the lid is air tight. Avoid direct sunlight on site.
Shelf-life	For at least 6 months if stored as above.

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.