

Product Datasheet

Eurorof Torch-On AVCL

Sheet No: PDS-RBM028
Issued: 28/02/2025
Pages: 1 of 1

Description

Eurorof Torch-On AVCL is a polyester reinforced, SBS modified bitumen vapour barrier with an aluminium core, with a polyethylene film on the underside and a sanded upper surface.

Use

For use as an air and vapour control layer in built-up roofing systems, in both new build and refurbishment projects.

Application

All surfaces to receive membrane must be clean and dry. Ensure that the membrane is accurately located, including overlaps. Fully bond by torch application.

Lap sizes: 100mm side, 150mm end.

Storage

Store upright in a clean, dry location, away from heat sources.

Product Data

Thickness	3.0 mm
Width	1.0 m
Length	10.0 m
Weight	4.0 kg/m ²
Weight per roll	40 kg

Performance Data

Tensile Strength – longitudinal	320 N/50mm
Tensile Strength – transverse	195 N/50mm
Elongation at break – longitudinal	30%
Softening point	100°C
Cold Flexibility	-15°C

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.