

# AIRTILE PLAIN

A Modern Flat Traditional Profile



ALUMASC  
ROOFING

## ✓ Where to Specify

- Educational Buildings
- Social Housing
- Commercial Buildings
- Flat to Pitch
- Community Centres
- Modular Buildings
- Vertical Cladding



# AIRTILE PLAIN

A Modern Flat Traditional Profile



ALUMASC  
ROOFING

## ✓ Advantages

- British made
- Designed to give a traditional slate appearance
- Lightweight
- Low pitch
- Good vandal resistance (0.9mm steel base)
- Quick installation
- Virtually maintenance free
- Extensive range of accessories and flashings available
- Fully dry-fixed
- 60+ Year life expectancy
- Guaranteed for 40-years against weather penetration


## ✓ Technical Data

- Minimum pitch 15°
- Maximum pitch 90°
- Overall width: 1320mm
- Cover width: 1260mm
- Side lap: 60mm
- Step: 20mm
- Batten gauge (0.45mm): 160mm
- Individual tile width: 180mm
- Roof cover per tile panel: 0.2m<sup>2</sup>
- Tile panels per m<sup>2</sup>: 5
- No. per m<sup>2</sup>: 0.45mm
- Weight as laid per m<sup>2</sup>: 8kg
- Fire resistance: AA classification equal to traditional roof tiles and slates

## ✓ Approvals

- BBA Certificate No. 02/3917
- Manufactured using ISO 9001 approved materials
- ISO 14001

## ✓ Colours Available




Titanium Grey




Bramble Brown




Rustic Brown




Rustic Terracotta



Moss Green



Tartan Green



## ✓ Technical Support

Alumasc Technical Services can advise on all aspects of product selection, specification and integration of Alumasc systems into any building design.