

# AIRTILE PROFILE

Profile to match many traditional roofs




ALUMASC  
ROOFING



## Where to Specify

- Educational Buildings
- Commercial Buildings
- Flat to Pitch
- Community Centres
- Vertical Cladding



# AIRTILE PROFILE

Profile to match many traditional roofs



**ALUMASC**  
ROOFING



## Technical Data

- Minimum pitch 10°
- Maximum pitch 90°
- Overall width: 1420mm
- Cover width: 1325mm
- Side lap: 105mm
- Step: 19mm
- Batten gauge (0.45mm): 365mm
- Batten gauge (0.9mm): 363mm
- Individual tile width: 165mm
- Roof cover per tile panel: 0.48m<sup>2</sup>
- Tile panels per m<sup>2</sup>: 2.08
- Steel base: 0.45mm & 0.9mm
- Weight as laid per m<sup>2</sup>: 7kg & 11kg
- Fire resistance: AA classification equal to traditional roof tiles and slates



## Advantages

- British made
- Designed to give a traditional slate appearance
- Lightweight
- Low pitch
- Good vandal resistance (0.9mm steel base)
- Quick installation / cost effective
- Virtually maintenance free
- Extensive range of accessories and flashings available
- Fully dry-fixed
- Guaranteed for 40-years against weather penetration



## Approvals

- BBA Certificate No. 02/3917
- Manufactured using ISO 9001 approved materials
- ISO 14001




## Warranties

Alumasc offers a comprehensive range of single-source warranty options for up to 50 Years. Installed exclusively by Registered Contractors and underpinned by Alumasc's extensive project support service.



## Colours Available




Titanium Grey




Bramble Brown




Rustic Brown



Rustic Terracotta



Tartan Green



## Technical Support

Alumasc Technical Services can advise on all aspects of product selection, specification and integration of Alumasc systems into any building design.



+44 (0)1744 648400



technical@alumascroofing.com



www.alumascroofing.com

Ref: SSDS-AIR006 Issued:07/03/25