

1. IDENTIFICATION OF THE SUBSTRATE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name/designation: Caltech Metprime Base

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Primer

1.3 Manufacturer/Supplier

Supplier:
Alumasc Building Products Ltd
White House Works, Bold Road, Sutton, St Helens, Merseyside, United Kingdom, WA9 4JG
Tel: +44 (0)1744 648400
e-mail: technical@alumascroofing.com

1.4 Emergency telephone number

Association / Organisation: National Poisons Information Service
Emergency telephone numbers: 0344 892 0111 (Healthcare professionals only)
Other emergency telephone numbers Alumasc Building Products: +44 17 4464 8400
(Mon-Thurs – 08.30-17.00 Fri – 08.30-16.00)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Considered a hazardous mixture according to Reg. (EC) No 1272/2008 and their amendments. Classified as Dangerous Goods for transport purposes.

Classification according to Regulation (EC) No. 1272/2008 [CLP][1]:

H336 - Specific target organ toxicity - single exposure Category 3 (narcotic effects), H411 - Chronic Aquatic Hazard Category 2, H225 - Flammable Liquid Category 2, H318 - Serious Eye Damage/Eye Irritation Category 1, H335 - Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), H315 - Skin Corrosion/Irritation Category 2, H317 - Skin Sensitizer Category 1

Legend:

1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567

2.2 Label elements

Hazard pictures:



Signal word:

Danger

Hazard statements:

H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.
H225: Highly flammable liquid and vapour.
H318: Causes serious eye damage.
H335: May cause respiratory irritation.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.

Supplementary statements:

Not Applicable.

Precautionary statements prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271: Use only a well-ventilated area.
P280: Wear protective gloves, protective clothing, eye protection and face protection.
P240: Ground and bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

P242: Use non-sparking tools.
P243: Take action to prevent static discharges.
P261: Avoid breathing mist/vapours/spray.
P273: Avoid release to the environment.
P264: Wash all exposed external body areas thoroughly after handling.
P272: Contaminated work clothing should not be allowed out of the workplace.

Precautionary statements response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/physician/first aider.
P370+P378: In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.
P302+P352: IF ON SKIN: Wash with plenty of water and soap.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P391: Collect spillage.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statements storage:

P403+P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.

Precautionary statements disposal:

P501: Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

2.3 Other hazards

naphtha petroleum,: Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)
light aromatic solvent
n-butanol: Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)
bisphenol A/ bisphenol: Listed in the Europe Regulation (EU) 2018/1881 Specific Requirements for Endocrine Disruptors.
A diglycidyl ether polymer
xylene: Listed in the Europe Regulation (EC) No 1907/2006 - Annex XVII (Restrictions may apply)

3. COMPOSITION AND INFORMATION ABOUT THE COMPONENTS

3.1 Substances

See 'Composition on ingredients' in Section 3.2

3.2 Mixtures

1.CAS No 2.EC No 3.Index No 4.REACH No	% [weight]	Name	Classified according to GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567	Nanoform Particle Characteristics
1.64742-95-6 2.265-199-0 3.649-356-00-4 4.Not Available	10-30	<u>naphtha</u> <u>petroleum, light</u> <u>aromatic solvent</u>	Flammable Liquid Category 3, Germ cell mutagenicity Category 1B, Carcinogenicity Category 1B, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Specific target organ toxicity - single exposure Category 3 (narcotic effects), Aspiration Hazard Category 1, Chronic Aquatic Hazard Category 2; H226, H340, H350, H335, H336, H304, H411, EUH066 [1]	Not Available
1.71-36-3 2.200-751-6 3.603-004-00-6 4.Not Available	10-30	<u>n-butanol</u>	Flammable Liquid Category 3, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 1, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Specific target organ toxicity -	Not Available

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

			single exposure Category 3 (narcotic effects); H226, H302, H315, H318, H335, H336 [2]	
1.25036-25-3 2.Not Available 3.Not Available 4.Not Available	5-10	bisphenol A/ bisphenol A diglycidyl ether polymer [e]	Skin Corrosion/Irritation Category 2, Eye Irritation Category 2, Skin Sensitizer Category 1, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation); H315, H319, H317, H335, EUH019 [1]	Not Available
1.7779-90-0 2.231-944-3 3.030-011-00-6 4.Not Available	1-5	zinc phosphate	Acute Aquatic Hazard Category 1, Chronic Aquatic Hazard Category 1; H400, H410 [2]	Not Available
1.1330-20-7 2.215-535-7 3.601-022-00-9 4.Not Available	1-5	xylene *	Flammable Liquid Category 3, Acute Toxicity (Dermal) Category 4, Acute Toxicity (Inhalation) Category 4, Skin Corrosion/Irritation Category 2; H226, H312, H332, H315 [2]	Not Available
1.1314-13-2 2.215-222-5 3.030-013-00-7 4.Not Available	<1	zinc oxide	Acute Aquatic Hazard Category 1, Chronic Aquatic Hazard Category 1; H400, H410 [2]	Not Available
1.147900-93-4 2.Not Available 3.Not Available 4.Not Available	<1	fatty acids, C18-unsatd., trimers, compds. with oleylamine	Skin Corrosion/Irritation Category 2, Eye Irritation Category 2, Skin Sensitizer Category 1, Specific target organ toxicity - repeated exposure Category 1, Chronic Aquatic Hazard Category 2; H315, H319, H317, H372, H411 [1]	Not Available
1.85711-55-3 2.288-315-1 3.Not Available 4.Not Available	<1	fatty acids, tall-oil, compounds with oleylamine	Serious Eye Damage/Eye Irritation Category 1, Skin Sensitizer Category 1, Specific target organ toxicity - repeated exposure Category 2, Chronic Aquatic Hazard Category 4; H318, H317, H373, H413 [1]	Not Available
Legend:	1. Classified by Chemwatch; 2. Classification drawn from GB-CLP Regulation, UK SI 2019/720 and UK SI 2020/1567; 3. Classification drawn from C&L; * EU IOELVs available; [e] Substance identified as having endocrine disrupting properties			

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye contact:

If this product comes in contact with the eyes:
Immediately hold eyelids apart and flush the eye continuously with running water.
Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
Transport to hospital or doctor without delay.
Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin contact:

If skin contact occurs:
Immediately remove all contaminated clothing, including footwear.
Flush skin and hair with running water (and soap if available).
Seek medical attention in event of irritation.

Inhalation:

If fumes or combustion products are inhaled remove from contaminated area.
Lay patient down. Keep warm and rested.
Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained.
Perform CPR if necessary.
Transport to hospital, or doctor, without delay.

Ingestion:

If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

If swallowed do NOT induce vomiting.

If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

Observe the patient carefully.

Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.

Seek medical advice.

Avoid giving milk or oils.

Avoid giving alcohol.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11.

4.3 Indication of any immediate medical attention and special treatment needed.

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For petroleum distillates

- In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption - decontamination (induced emesis or lavage) is controversial and should be considered on the merits of each individual case; of course the usual precautions of an endotracheal tube should be considered prior to lavage, to prevent aspiration.
- Individuals intoxicated by petroleum distillates should be hospitalized immediately, with acute and continuing attention to neurologic and cardiopulmonary function.
- Positive pressure ventilation may be necessary.
- Acute central nervous system signs and symptoms may result from large ingestions of aspiration-induced hypoxia.
- After the initial episode, individuals should be followed for changes in blood variables and the delayed appearance of pulmonary oedema and chemical pneumonitis. Such patients should be followed for several days or weeks for delayed effects, including bone marrow toxicity, hepatic and renal impairment. Individuals with chronic pulmonary disease will be more seriously impaired, and recovery from inhalation exposure may be complicated.
- Gastrointestinal symptoms are usually minor and pathological changes of the liver and kidneys are reported to be uncommon in acute intoxications
- Chlorinated and non-chlorinated hydrocarbons may sensitize the heart to epinephrine and other circulating catecholamines so that arrhythmias may occur. Careful consideration of this potential adverse effect should precede administration of epinephrine or other cardiac stimulants and the selection of bronchodilators.

BP America Product Safety & Toxicology Department

To treat poisoning by the higher aliphatic alcohols (up to C7):

- Gastric lavage with copious amounts of water.
- It may be beneficial to instill 60 ml of mineral oil into the stomach.
- Oxygen and artificial respiration as needed.
- Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5]

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for shock.
- Monitor and treat, where necessary, for pulmonary oedema.
- Anticipate and treat, where necessary, for seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- Give activated charcoal.

ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

- Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.
- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- Acidosis may respond to hyperventilation and bicarbonate therapy.
- Haemodialysis might be considered in patients with severe intoxication.
- Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above.

Symptomatic and supportive therapy is advised in managing patients.

For acute or short term repeated exposures to xylene:

- Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- Pulmonary absorption is rapid with about 60-65% retained at rest.
- Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ < 50 mm Hg or pCO₂ > 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
Methylhippu-ric acids in urine	1.5 gm/gm creatinine 2 mg/min	End of shift Last 4 hrs of shift	

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).

5.2 Special hazards arising from the substance or mixture

Fire incompatibility:

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

5.3 Advice for fire-fighters

Fire-fighting:

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves in the event of a fire.

Fire/explosion hazard:

- Liquid and vapour are highly flammable.
- Fire hazard when exposed to heat, flame and/or oxidisers.

Combustion products include:

- carbon dioxide (CO₂)
- aldehydes
- metal oxides
- other pyrolysis products typical of burning organic material.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

See Section 8.

6.2 Environmental Precautions

See Section 12.

6.3 Methods and material for containment and cleaning up

Minor spills:

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.

Major spills:

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.

6.4 Reference to other sections

Personal Protective Equipment advice is contained in Section 8 of the SDS.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Safe handling:

The conductivity of this material may make it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec).
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- **DO NOT allow clothing wet with material to stay in contact with skin**

Fire & explosion protection:

See Section 5.

Other information:

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- **DO NOT store in pits, depressions, basements or areas where vapours may be trapped.**

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

7.2 Conditions for safe storage, including any incompatibilities

Suitable container:

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt.

Storage incompatibility:

Xylenes:

- may ignite or explode in contact with strong oxidisers, 1,3-dichloro-5,5-dimethylhydantoin, uranium fluoride
- attack some plastics, rubber and coatings
- may generate electrostatic charges on flow or agitation due to low conductivity.
- Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents.
- Aromatics can react exothermically with bases and with diazo compounds.

For alkyl aromatics:

The alkyl side chain of aromatic rings can undergo oxidation by several mechanisms. The most common and dominant one is the attack by oxidation at benzylic carbon as the intermediate formed is stabilised by resonance structure of the ring.








- Following reaction with oxygen and under the influence of sunlight, a hydroperoxide at the alpha-position to the aromatic ring, is the primary oxidation product formed (provided a hydrogen atom is initially available at this position)
 - this product is often short-lived but may be stable dependent on the nature of the aromatic substitution; a secondary C-H bond is more easily attacked than a primary C-H bond whilst a tertiary C-H bond is even more susceptible to attack by oxygen
- Monoalkylbenzenes may subsequently form monocarboxylic acids; alkyl naphthalenes mainly produce the corresponding naphthalene carboxylic acids.

Alcohols

- are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.
- reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen
- react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium
- should not be heated above 49 deg. C. when in contact with aluminium equipment

Glycidyl ethers:

- may form unstable peroxides on storage in air, light, sunlight, UV light or other ionising radiation, trace metals - inhibitor should be
- maintained at adequate levels
- may polymerise in contact with heat, organic and inorganic free radical producing initiators
- may polymerise with evolution of heat in contact with oxidisers, strong acids, bases and amines
- react violently with strong oxidisers, permanganates, peroxides, acyl halides, alkalis, ammonium persulfate, bromine dioxide
- attack some forms of plastics, coatings, and rubber

						
+	X	+	X	+	+	+

X - Must not be stored together.

O - May be stored together with specific preventions.

+ - May be stored together.

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

7.3 Specific end uses(s)

See Section 1.2.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Ingredient	DNELs Exposure Pattern Worker	PNECs Compartment
naphtha petroleum, light aromatic solvent	Inhalation 837.5 mg/m ³ (Local, Chronic) Inhalation 1 286.4 mg/m ³ (Systemic, Acute) Inhalation 1 066.67 mg/m ³ (Local, Acute) <i>Inhalation 178.57 mg/m³ (Local, Chronic) *</i> <i>Inhalation 1 152 mg/m³ (Systemic, Acute) *</i> <i>Inhalation 640 mg/m³ (Local, Acute) *</i>	Not Available
n-butanol	Inhalation 310 mg/m ³ (Local, Chronic) <i>Dermal 3.125 mg/kg bw/day (Systemic, Chronic) *</i> <i>* Inhalation 55.357 mg/m³ (Systemic, Chronic) *</i> <i>Oral 1.562 mg/kg bw/day (Systemic, Chronic) *</i> <i>Inhalation 155 mg/m³ (Local, Chronic) *</i>	0.082 mg/L (Water (Fresh)) 0.008 mg/L (Water - Intermittent release) 2.25 mg/L (Water (Marine)) 0.324 mg/kg sediment dw (Sediment (Fresh Water)) 0.032 mg/kg sediment dw (Sediment (Marine)) 0.017 mg/kg soil dw (Soil) 2476 mg/L (STP)
zinc phosphate	Dermal 83 mg/kg bw/day (Systemic, Chronic) Inhalation 5 mg/m ³ (Systemic, Chronic) <i>Dermal 83 mg/kg bw/day (Systemic, Chronic) *</i> <i>Inhalation 2.5 mg/m³ (Systemic, Chronic) *</i> <i>Oral 0.83 mg/kg bw/day (Systemic, Chronic) *</i>	20.6 µg/L (Water (Fresh)) 6.1 µg/L (Water - Intermittent release) 117.8 mg/kg sediment dw (Sediment (Fresh Water)) 56.5 mg/kg sediment dw (Sediment (Marine)) 35.6 mg/kg soil dw (Soil) 100 µg/L (STP)
xylene	Dermal 212 mg/kg bw/day (Systemic, Chronic) Inhalation 221 mg/m ³ (Systemic, Chronic) Inhalation 221 mg/m ³ (Local, Chronic) Inhalation 442 mg/m ³ (Systemic, Acute) Inhalation 442 mg/m ³ (Local, Acute) <i>Dermal 125 mg/kg bw/day (Systemic, Chronic) *</i> <i>Inhalation 65.3 mg/m³ (Systemic, Chronic) *</i> <i>Oral 12.5 mg/kg bw/day (Systemic, Chronic) *</i> <i>Inhalation 65.3 mg/m³ (Local, Chronic) *</i> <i>Inhalation 260 mg/m³ (Systemic, Acute) *</i> <i>Inhalation 260 mg/m³ (Local, Acute) *</i>	0.327 mg/L (Water (Fresh)) 0.327 mg/L (Water - Intermittent release) 0.327 mg/L (Water (Marine)) 12.46 mg/kg sediment dw (Sediment (Fresh Water)) 12.46 mg/kg sediment dw (Sediment (Marine)) 2.31 mg/kg soil dw (Soil) 6.58 mg/L (STP)
zinc oxide	Dermal 83 mg/kg bw/day (Systemic, Chronic) Inhalation 5 mg/m ³ (Systemic, Chronic) Inhalation 0.5 mg/m ³ (Local, Chronic) <i>Dermal 83 mg/kg bw/day (Systemic, Chronic) *</i> <i>Inhalation 2.5 mg/m³ (Systemic, Chronic) *</i> <i>Oral 0.83 mg/kg bw/day (Systemic, Chronic) *</i>	0.19 µg/L (Water (Fresh)) 1.14 µg/L (Water - Intermittent release) 1.2 µg/L (Water (Marine)) 18 mg/kg sediment dw (Sediment (Fresh Water)) 6.4 mg/kg sediment dw (Sediment (Marine)) 0.7 mg/kg soil dw (Soil) 20 µg/L (STP) 0.16 mg/kg food (Oral)
fatty acids, C18-unsatd., trimers, compds. with oleylamine	Dermal 0.024 mg/kg bw/day (Systemic, Chronic) Dermal 0.012 mg/kg bw/day (Systemic, Chronic)* Oral 0.012 mg/kg bw/day (Systemic, Chronic)*	6 µg/L (Water (Fresh)) 0.6 µg/L (Water - Intermittent release) 2.46 mg/kg sediment dw (Sediment (Fresh Water)) 0.25 mg/kg sediment dw (Sediment (Marine)) 0.28 mg/kg soil dw (Soil) 0.47 mg/kg food (Oral)

fatty acids, tall-oil, compounds with oleylamine	Dermal 0.024 mg/kg bw/day (Systemic, Chronic) Dermal 0.012 mg/kg bw/day (Systemic, Chronic)* Oral 0.012 mg/kg bw/day (Systemic, Chronic)*	0.47 mg/kg food (Oral)
--	---	------------------------

* Values for general population.

Occupational Exposure Limits (OEL):

Ingredient data:

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)	n-butanol	Butan-1-ol	Not Available	154 mg/m ³ / 50 ppm	Not Available	Sk
UK Workplace Exposure Limits (WELs)	xylene	Xylene (mixed isomers, pure)	50 ppm / 221 mg/m ³	442 mg/m ³ / 100 ppm	Not Available	Skin
UK Workplace Exposure Limits (WELs)	xylene	Xylene, o-,m-,p- or mixed isomers	50 ppm / 220 mg/m ³	441 mg/m ³ / 100 ppm	Not Available	Sk, BMGV

Emergency limits:

Ingredient	TEEL-1	TEEL-2	TEEL-3
naphtha petroleum, light aromatic solvent	1,200 mg/m ³	6,700 mg/m ³	40,000 mg/m ³
n-butanol	60 ppm	800 ppm	8000** ppm
bisphenol A/ bisphenol A diglycidyl ether polymer	12 mg/m ³	130 mg/m ³	790 mg/m ³
zinc phosphate	12 mg/m ³	36 mg/m ³	220 mg/m ³
xylene	Not Available	Not Available	Not Available
zinc oxide	10 mg/m ³	15 mg/m ³	2,500 mg/m ³

Ingredient	Original IDLH	Revised IDLH
naphtha petroleum, light aromatic solvent	Not Available	Not Available
n-butanol	1,400 ppm	Not Available
bisphenol A/ bisphenol A diglycidyl ether polymer	Not Available	Not Available
zinc phosphate	Not Available	Not Available
xylene	900 ppm	Not Available
zinc oxide	500 mg/m ³	Not Available
fatty acids, C18-unsatd., trimers, compds. with oleylamine	Not Available	Not Available
fatty acids, tall-oil, compounds with oleylamine	Not Available	Not Available

Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
naphtha petroleum, light aromatic solvent	E	≤ 0.1 ppm
bisphenol A/ bisphenol A diglycidyl ether polymer	E	≤ 0.1 ppm
zinc oxide	E	≤ 0.01 mg/m ³
fatty acids, C18-unsatd., trimers, compds. with oleylamine	E	≤ 0.1 ppm

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

fatty acids, tall-oil, compounds with oleylamine	E	≤ 0.1 ppm
Notes:	<i>Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.</i>	

8.2 Exposure controls

8.2.1. Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.
8.2.2. Personal protection	
Eye and face protection:	Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection:	See Hand Protection below.
Hands/feet protection:	NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. When handling liquid-grade epoxy resins wear chemically protective gloves, boots and aprons. The performance, based on breakthrough times, of: ·Ethyl Vinyl Alcohol (EVAL laminate) is generally excellent ·Butyl Rubber ranges from excellent to good ·Nitrile Butyl Rubber (NBR) from excellent to fair. ·Neoprene from excellent to fair ·Polyvinyl (PVC) from excellent to poor As defined in ASTM F-739-96 ·Excellent breakthrough time > 480 min ·Good breakthrough time > 20 min ·Fair breakthrough time < 20 min ·Poor glove material degradation Gloves should be tested against each resin system prior to making a selection of the most suitable type.
Body protection:	See Other Protection below.
Other protection:	Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered.

Respiratory protection	<p>Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)</p> <p>Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.</p> <p>The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.</p> <p>Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used</p>
-------------------------------	---

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the: "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computer generated selection: Eurorof Spray Cleaning Solvent

Materia	CPI	Materia	CPI
PE/EVAL/PE	A	NEOPRENE	C
PVA	A	NEOPRENE/NATURAL	C
TEFLON	A	NITRILE	C
BUTYL	C	NITRILE+PVC	C
BUTYL/NEOPRENE	C	PE	C
HYPALON	C	PVC	C
NAT+NEOPR+NITRILE	C	PVDC/PE/PVDC	C
NATURAL RUBBER	C	VITON	C
NATURAL+NEOPRENE	C	NEOPRENE	C
PE/EVAL/PE	A		

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

8.2.3. Environmental exposure controls:

See Section 12.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Important health, safety and environmental information

Appearance:	Various colours		
Physical state:	Liquid	Relative density (Water = 1):	1.3-1.4
Odour:	Characteristic	Partition coefficient n-octanol/water:	Not Available
Odour threshold:	Not Available	Auto-ignition temperature (°C):	Not Available
pH (as supplied):	Not Available	Decomposition temperature:	Not Available
Melting point/freezing point (°C):	Not Available	Viscosity (cSt):	Not Available
Initial boiling point and boiling range (°C):	Not Available	Molecular weight (g/mol):	Not Available
Flash point (°C):	21-23	Taste:	Not Available
Evaporation rate:	Not Available	Explosive properties:	Not Available
Flammability:	HIGHLY FLAMMABLE.	Oxidising properties:	Not Available
Upper Explosive Limit (%):	Not Available	Surface Tension (dyn/cm or mN/m):	Not Available
Lower Explosive Limit (%):	Not Available	Volatile Component (%vol):	Not Available

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

Vapour pressure (kPa):	Not Available	Gas group:	Not Available
Solubility in water:	Immiscible	pH as a solution (1%):	Not Available
Vapour density (Air = 1):	>1	VOC g/L:	Not Available
Nanoform Solubility	Not Available	Nanoform Particle Characteristics	Not Available
Particle Size	Not Available		

9.2 Other information

Not Available

10. STABILITY AND REACTIVITY

10.1 Reactivity

See Section 7.2.

10.2 Chemical stability

Unstable in the presence of incompatible materials.
Product is considered stable.
Hazardous polymerisation will not occur.

10.3 Possibility of hazardous reactions

See Section 7.2.

10.4 Conditions to avoid

See Section 7.2.

10.5 Incompatible materials

See Section 7.2.

10.6 Hazardous decomposition products

See Section 5.3

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Inhaled:	<p>The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.</p> <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Exposure to n-butanol causes dose dependent irritation and headaches in humans, but CNS depression and prostration in mice. Though the offensive odour may forewarn, the smell sense may become fatigued.</p> <p>Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow.</p> <p>The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence.</p> <p>Inhalation hazard is increased at higher temperatures.</p> <p>Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and light-headedness. Low molecular weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor.</p> <p>Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> <p>On exposure to mixed trimethylbenzenes, some people may become nervous, tensed, anxious and have difficult breathing. There may be a reduction red blood cells and bleeding abnormalities. There may also be drowsiness.</p>
-----------------	--

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

	<p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p>The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, ringing in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Headache, fatigue, tiredness, irritability and digestive disturbances (nausea, loss of appetite and bloating) are the most common symptoms of xylene overexposure. Injury to the heart, liver, kidneys and nervous system has also been noted amongst workers.</p> <p>Xylene is a central nervous system depressant</p>
Ingestion:	<p>Reactive diluents exhibit a range of ingestion hazards. Small amounts swallowed incidental to normal handling operations are not likely to cause injury. However, swallowing larger amounts may cause injury.</p> <p>Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and inco-ordination, giddiness, confusion, delirium and coma.</p> <p>Animal testing showed that a single dose of bisphenol A diglycidyl ether (BADGE) given by mouth, caused an increase in immature sperm.</p> <p>Swallowing of n-butanol may cause breathing difficulties, headache, nausea, vomiting, irritation of the airway and mucous membranes as well as depression of the central nervous system.</p> <p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p> <p>The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.</p> <p>Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions.</p> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p>
Skin contact:	<p>The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p> <p>Bisphenol A diglycidyl ether (BADGE) may produce contact dermatitis characterized by redness and swelling, with weeping followed by crusting and scaling. A liquid resin with a molecular weight of 350 produced severe skin irritation when applied daily for 4 hours over 20 days.</p> <p>Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.</p> <p>Aromatic hydrocarbons may produce sensitivity and redness of the skin. They are not likely to be absorbed into the body through the skin but branched species are more likely to.</p>
Eye:	<p>If applied to the eyes, this material causes severe eye damage.</p> <p>N-butanol can cause eye damage, burning sensation, blurring of vision, excessive tear formation and discomfort to bright light.</p> <p>Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion.</p>
Chronic:	<p>Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems.</p> <p>Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.</p> <p>Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.</p> <p>Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.</p> <p>Bisphenol A diglycidyl ethers (BADGEs) produce a sensitization dermatitis (skin inflammation) characterized by eczema with blisters and papules, with considerable itching of the back of the</p>

	<p>hand. This may persist for 10-14 days after withdrawal from exposure and recur immediately on re-exposure. The dermatitis may last longer following each exposure, but is unlikely to become more intense.</p> <p>For some reactive diluents, prolonged or repeated skin contact may result in absorption of potentially harmful amounts or allergic skin reactions.</p> <p>Exposure to some reactive diluents (notably, neopentylglycol diglycidyl ether, CAS RN: 17557-23-2) has caused cancer in some animal testing.</p> <p>Bisphenol A may have effects similar to female sex hormones and when administered to pregnant women, may damage the foetus. It may also damage male reproductive organs and sperm.</p> <p>Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function.</p> <p>Skin exposure may result in drying and cracking and redness of the skin.</p> <p>Hearing and balance loss have been reported with exposure to n-butanol, especially with concomitant long term unprotected exposure to high noise.</p> <p>Glycidyl ethers can cause genetic damage and cancer.</p> <p>There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.</p> <p>Women exposed to xylene in the first 3 months of pregnancy showed a slightly increased risk of miscarriage and birth defects. Evaluation of workers chronically exposed to xylene has demonstrated lack of genetic toxicity.</p> <p>Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.</p>
--	--

Caltech Metprime Base:

Toxicity	Irritation
Not available	Not available

naphtha petroleum, light aromatic solvent:

Toxicity	Irritation
Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
Inhalation(Rat) LC50; >4.42 mg/L4h ^[1]	Skin: adverse effect observed (irritating) ^[1]
Oral(Rat) LD50; >4500 mg/kg ^[1]	

n-butanol:

Toxicity	Irritation
Dermal (rabbit) LD50: ~3430 mg/kg ^[1]	Eye (human): 50 ppm - irritant
Inhalation(Rat) LC50; >17.76 mg/l4h ^[2]	Eye (rabbit): 1.6 mg-SEVERE
Oral(Mouse) LD50; 100 mg/kg ^[2]	Eye (rabbit): 24 mg/24h-SEVERE
	Eye: adverse effect observed (irreversible damage) ^[1]
	Skin (rabbit): 405 mg/24h-moderate
	Skin: adverse effect observed (irritating) ^[1]

bisphenol A/ bisphenol A diglycidyl ether polymer:

Toxicity	Irritation
dermal (rat) LD50: >2000 mg/kg ^[2]	Not Available
Oral(Rat) LD50; >2000 mg/kg ^[2]	

zinc phosphate:

Toxicity	Irritation
Oral(Rat) LD50; >5000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Skin: no adverse effect observed (not irritating) ^[1]

Xylene:

Toxicity	Irritation
Dermal (rabbit) LD50: >1700 mg/kg ^[2]	Eye (human): 200 ppm irritant
Inhalation(Rat) LC50; 5922 ppm4h ^[1]	Eye (rabbit): 5 mg/24h SEVERE
Oral(Mouse) LD50; 2119 mg/kg ^[2]	Eye (rabbit): 87 mg mild
	Eye: adverse effect observed (irritating) ^[1]
	Skin (rabbit):500 mg/24h moderate
	Skin: adverse effect observed (irritating) ^[1]

zinc oxide:

Toxicity	Irritation
dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit) : 500 mg/24 h - mild
Inhalation(Rat) LC50; >1.79 mg/l4h ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
Oral(Rat) LD50; >5000 mg/kg ^[1]	Skin (rabbit) : 500 mg/24 h- mild
	Skin: no adverse effect observed (not irritating) ^[1]

fatty acids, C18-unsatd., trimers, compds. witholeylamine:

Toxicity	Irritation
Oral(Rat) LD50; >1570 mg/kg ^[1]	Not Available

fatty acids, tall-oil,compounds with oleylamine:

Toxicity	Irritation
Oral(Rat) LD50; >2000 mg/kg ^[1]	Eye : Severe *
	Eye: adverse effect observed (irreversible damage) ^[1]
	Skin : Not irritating *
	Skin: no adverse effect observed (not irritating) ^[1]

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity; 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances.

Caltech Metprime Base	<p>Data demonstrate that during inhalation exposure,aromatic hydrocarbons undergo substantial partitioning into adipose tissues. Following cessation of exposure, the level of aromatic hydrocarbons in body fats rapidly declines. Thus, the aromatic hydrocarbons are unlikely to bioaccumulate in the body.</p> <p>Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins.</p> <p>The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species. In many cases, the hydrophobic hydrocarbons are ingested in association with fats in the diet.</p> <p>The various members of the bisphenol family produce hormone like effects, seemingly as a result of binding to estrogen receptor-related receptors (ERRs; not to be confused with estrogen receptors)</p> <p>A suspected estrogen-related receptors (ERR) binding agent: Estrogen-related receptors (ERR, oestrogen-related receptors) are so named because of sequence homology with estrogen receptors but do not appear to bind estrogens or other tested steroid hormones. The ERR family have been demonstrated to control energy homeostasis, oxidative metabolism and mitochondrial biogenesis ,while effecting mammalian physiology in the heart, brown adipose tissue, white adipose tissue, placenta, macrophages, and demonstrated additional roles in diabetes and cancer.</p> <p>ERRs bind enhancers throughout the genome where they exert effects on gene regulation Although their overall functions remain uncertain, they also share DNA-binding sites, co-regulators, and target genes with the conventional estrogen receptors ERalpha and ERbeta and may function to modulate estrogen signaling pathways.</p> <p>· ERR-alpha has wide tissue distribution but it is most highly expressed in tissues that preferentially use fatty acids as energy sources such as kidney, heart, brown adipose tissue, cerebellum, intestine, and skeletal muscle. ERRalpha has been detected in normal adrenal cortex tissues, in which its expression is possibly related to adrenal development, with a possible role in fetal adrenal function, in dehydroepiandrosterone (DHEAS) production in adrenarache, and also in steroid production of post-adrenarache/adult life. DHEA and other adrenal androgens such as androstenedione, although relatively weak androgens, are responsible for the androgenic effects of adrenarache, such as early pubic and axillary hair growth, adult-type body odor, increased oiliness of hair and skin, and mild acne.</p> <p>Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) share many common characteristics with respect to animal toxicology. One such oxirane is ethyloxirane; data presented here may be taken as representative.</p>
------------------------------	--

NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	For C9 aromatics (typically trimethylbenzenes – TMBs) Acute toxicity: Animal testing shows that semi-lethal concentrations and doses vary amongst this group. The semilethal concentrations for inhalation range from 6000 to 10000 mg/cubic metre for C9 aromatic naphtha and 18000-24000 mg/cubic metre for 1,2,4- and 1,3,5-TMB, respectively. Irritation and sensitization: Results from animal testing indicate that C9 aromatic hydrocarbon solvents are mildly to moderately irritating to the skin, minimally irritating to the eye, and have the potential to irritate the airway and cause depression of breathing rate. There is no evidence that it sensitizes skin. Repeated dose toxicity: Animal studies show that chronic inhalation toxicity for C9 aromatic hydrocarbon solvents is slight. * [Devoe] .
N-BUTANOL	For n-butanol: Acute toxicity: In animal testing, n-butanol (BA) was only slightly toxic, following exposure by swallowing, skin contact or irritation. Animal testing and human experience suggest that n-butanol is moderately irritating to the skin but severely irritating to the eye. Human studies show that BA is not likely to cause skin sensitization.
BISPHENOL A/ BISPHENOL A DIGLYCIDYL ETHER POLYMER	*Hexion MSDS Epikote 1001
XYLENE	Reproductive effector in rats The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.
FATTY ACIDS, C18- UNSATD., TRIMERS, COMPDS. WITH OLEYLAMINE	FND ether amines and FND amines are very similar in structure (length of chain or degree of saturation), function and toxicity. Acute exposure to FND ether amines by oral, dermal and inhalation may produce moderate to slight toxicity but repeated skin contact can be highly irritating. However, exposure did not produce any organ-specific toxicity, genetic, reproductive or developmental defect same as in FND amines.
FATTY ACIDS, TALL-OIL, COMPOUNDS WITH OLEYLAMINE	Fatty acid salts of low acute toxicity. Their potential to irritate the skin and eyes is dependent on chain length. Eye irritation, rabbit : Mean irritation score 24, 48 and 72 h for each of 3 animals: 1.3 to 2.7 for corneal opacity; 1.0 for iris lesion; 2.7 to 3.0 for redness of conjunctivae; 2.0 to 3.3 for oedema. Skin sensitisation: During the pre-screen test, increases in ear thickening by more than 25% were recorded in all animals treated at 10% w/v and higher concentrations, whereas in animals treated at 1% w/v an increase in ear thickness was not evident or less than 25%. No eodema were observed up to the highest concentration of 100%. In the reproduction and developmental toxicity screening study (OECD 422) - the no effect level (NOEL) for reproductive toxicity was derived at the dose of 75 mg/kg/day, i.e. the highest dose level that could be applied to the animals based on general toxic effects. The no-adverse-effect-level (NOAEL) for adult animals and specifically maternal toxicity was 7.1 mg/kg/day. This NOAEL was derived mainly from histopathology findings in nulliparous, nonpregnant females after 5 weeks of treatment, because, in general, histopathology was not conducted on dams. * REACH Dossier
Caltech Metprime Base & NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT & N-BUTANOL & BISPHENOL A/ BISPHENOL A DIGLYCIDYL ETHER POLYMER	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant.
Caltech Metprime Base & BISPHENOL A/ BISPHENOL A DIGLYCIDYL ETHER POLYMER & FATTY ACIDS, C18- UNSATD., TRIMERS, COMPDS. WITH OLEYLAMINE & FATTY ACIDS, TALL-OIL, COMPOUNDS WITH OLEYLAMINE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.
Caltech Metprime Base & BISPHENOL A/ BISPHENOL A DIGLYCIDYL ETHER POLYMER	Animal testing over 13 weeks showed bisphenol A diglycidyl ether (BADGE) caused mild to moderate, chronic, inflammation of the skin. Reproductive and Developmental Toxicity: Animal testing showed BADGE given over several months caused reduction in body weight but had no reproductive effects. Cancer-causing potential: It has been concluded that bisphenol A diglycidyl ether

	cannot be classified with respect to its cancer-causing potential in humans. Genetic toxicity: Laboratory tests on genetic toxicity of BADGE have so far been negative. Immunotoxicity: Animal testing suggests regular injections of diluted BADGE may result in sensitization. Consumer exposure: Consumer exposure to BADGE is almost exclusively from migration of BADGE from can coatings into food. The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon. This class of endocrine disruptors that mimic oestrogens is widely used in industry, particularly in plastics. Bisphenol A (BPA) and some related compounds exhibit oestrogenic activity in human breast cancer cell line MCF-7, but there were remarkable differences in activity. Several derivatives of BPA exhibited significant thyroid hormonal activity towards rat pituitary cell line GH3, which releases growth hormone in a thyroid hormone-dependent manner.
Caltech Metprime Base & NAPHTHA PETROLEUM, LIGHT AROMATIC SOLVENT	For trimethylbenzenes: Absorption of 1,2,4-trimethylbenzene occurs after exposure by swallowing, inhalation, or skin contact. In the workplace, inhalation and skin contact are the most important routes of absorption; whole-body toxic effects from skin absorption are unlikely to occur as the skin irritation caused by the chemical generally leads to quick removal. The substance is fat-soluble and may accumulate in fatty tissues.
N-BUTANOL & XYLENE	The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
N-BUTANOL & XYLENE & ZINC OXIDE	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
BISPHENOL A/ BISPHENOL A DIGLYCIDYL ETHER POLYMER & FATTY ACIDS, C18-UNSATD., TRIMERS, COMPDS. WITH OLEYLAMINE	No significant acute toxicological data identified in literature search.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin Sensitisation	✓	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend:

- ✗** - Data either not available or does not fill the criteria for classification.
- ✓** - Data available to make classification.

11.2.1. Endocrine Disruption Properties

Many chemicals may mimic or interfere with the body's hormones, known as the endocrine system. Endocrine disruptors are chemicals that can interfere with endocrine (or hormonal) systems.

Endocrine disruptors interfere with the synthesis, secretion, transport, binding, action, or elimination of natural hormones in the body. Any system in the body controlled by hormones can be derailed by hormone disruptors. Specifically, endocrine disruptors may be associated with the development of learning disabilities, deformations of the body various cancers and sexual development problems.

Endocrine disrupting chemicals cause adverse effects in animals. But limited scientific information exists on potential health problems in humans. Because people are typically exposed to multiple endocrine disruptors at the same time, assessing public health effects is difficult.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Caltech Metprime Base:

End point	Test duration (Hr)	Species	Value	Source
Not available	Not available	Not available	Not available	Not available

naphtha petroleum, light aromatic solvent:

End point	Test duration (Hr)	Species	Value	Source
NOEC(ECx)	72h	Algae or other aquatic plants	1mg/l	1
EC50	72h	Algae or other aquatic plants	19mg/l	1
EC50	48h	Crustacea	6.14mg/l	1
EC50	96h	Algae or other aquatic plants	64mg/l	2

n-butanol:

End point	Test duration (Hr)	Species	Value	Source
NOEC(ECx)	504h	Crustacea	4.1mg/l	2
EC50	72h	Algae or other aquatic plants	>500mg/l	1
LC50	96h	Fish	100-500mg/l	4
EC50	48h	Crustacea	>500mg/l	1
EC50	96h	Algae or other aquatic plants	225mg/l	2

bisphenol A/ bisphenol A diglycidyl ether polymer:

End point	Test duration (Hr)	Species	Value	Source
Not available	Not available	Not available	Not available	Not available

zinc phosphate:

End point	Test duration (Hr)	Species	Value	Source
EC50(ECx)	24h	Crustacea	0.22mg/l	2
LC50	48h	Crustacea	>1.08mg/l	2

xylene:

End point	Test duration (Hr)	Species	Value	Source
EC50	72h	Algae or other aquatic plants	4.6mg/l	2
LC50	96h	Fish	2.6mg/l	2
EC50	48h	Crustacea	1.8mg/l	2
NOEC(ECx)	73h	Algae or other aquatic plants	0.44mg/l	2

zinc oxide:

End point	Test duration (Hr)	Species	Value	Source
EC50	72h	Algae or other aquatic plants	0.036-0.049mg/l	4
BCF	1344h	Fish	19-110	7
LC50	96h	Fish	0.927-2.589mg/l	4
EC50	48h	Crustacea	0.301-0.667mg/l	4
NOEC(ECx)	72h	Algae or other aquatic plants	0.005mg/l	2

fatty acids, C18-unsatd., trimers, compds. With oleylamine:

End point	Test duration (Hr)	Species	Value	Source
Not Available	Not Available	Not Available	Not Available	Not Available

fatty acids, tall-oil, compounds with oleylamine:

End point	Test duration (Hr)	Species	Value	Source
NOEC(ECx)	504h	Crustacea	>=2.3<4.6mg/l	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

When spilled this product may act as a typical oil, causing a film, sheen, emulsion or sludge at or beneath the surface of the body of water. The oil film on water surface may physically affect the aquatic organisms, due to the interruption of the oxygen transfer between the air and the water

Oils of any kind can cause:

- drowning of water-fowl due to lack of buoyancy, loss of insulating capacity of feathers, starvation and vulnerability to predators due to lack of mobility
- lethal effects on fish by coating gill surfaces, preventing respiration
- asphyxiation of benthic life forms when floating masses become engaged with surface debris and settle on the bottom and

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

adverse aesthetic effects of fouled shoreline and beaches
In case of accidental releases on the soil, a fine film is formed on the soil, which prevents the plant respiration process and the soil particle saturation. It may cause deep water infestation.

For 1,2,4 - Trimethylbenzene:

Half-life (hr) air: 0.48-16;

Half-life (hr) H₂O surface water: 0.24 -672;

Half-life (hr) H₂O ground: 336-1344;

Half-life (hr) soil: 168-672;

Henry's Pa m³ /mol: 385 -627;

Bioaccumulation: not significant. 1,2,4-Trimethylbenzene is a volatile organic compound (VOC) substance.

Atmospheric Fate: 1,2,4-trimethylbenzene can contribute to the formation of photochemical smog in the presence of other VOCs.

For Aromatic Substances Series:

Environmental Fate: Large, molecularly complex polycyclic aromatic hydrocarbons, or PAHs, are persistent in the environment longer than smaller PAHs.

Atmospheric Fate: PAHs are 'semi-volatile substances' which can move between the atmosphere and the Earth's surface in repeated, temperature-driven cycles of deposition and volatilization. Terrestrial Fate: BTEX compounds have the potential to move through soil and contaminate ground water, and their vapors are highly flammable and explosive.

For bisphenol A and related bisphenols:

Environmental fate:

Biodegradability (28 d) 89% - Easily biodegradable

Bioconcentration factor (BCF) 7.8 mg/l

Bisphenol A, its derivatives and analogues, can be released from polymers, resins and certain substances by metabolic products

Substance does not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII

As an environmental contaminant, bisphenol A interferes with nitrogen fixation at the roots of leguminous plants associated with the bacterial symbiont *Sinorhizobium meliloti*. Despite a half-life in the soil of only 1-10 days, its ubiquity makes it an important pollutant. According to Environment Canada, "initial assessment shows that at low levels, bisphenol A can harm fish and organisms over time.

For petroleum distillates:

Environmental fate:

When petroleum substances are released into the environment, four major fate processes will take place: dissolution in water, volatilization, biodegradation and adsorption. These processes will cause changes in the composition of these UVCB substances. In the case of spills on land or water surfaces, photodegradation-another fate process-can also be significant.

For C9 aromatics (typically trimethylbenzene - TMBs)

Chemicals in this category possess properties indicating a hazard for the environment (acute toxicity for fish, invertebrates, and algae from 1 to 10 mg/L). Category members are readily biodegradable, except 1,3,5-trimethylbenzene (CAS RN 108-67-8). Category members are not expected to be bioaccumulative.

Significant environmental findings are limited. Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit common characteristics with respect to environmental fate and ecotoxicology. One such oxirane is ethyloxirane and data presented here may be taken as representative.

For 1,2-Butylene oxide (Ethyloxirane):

log Kow values of 0.68 and 0.86. BAF and BCF : 1 to 17 L./kg.

Aquatic Fate - Ethyloxirane is highly soluble in water and has a very low soil-adsorption coefficient, which suggests that, if released to water, adsorption of ethyloxirane to sediment and suspended solids is not expected.

For Surfactants: Kow cannot be easily determined due to hydrophilic/hydrophobic properties of the molecules in surfactants. BCF value: 1-350.

Aquatic Fate: Surfactants tend to accumulate at the interface of the air with water and are not extracted into one or the other liquid phases.

For Xylenes:

log Koc : 2.05-3.08; Koc : 25.4-204; Half-life (hr) air : 0.24-42; Half-life (hr) H₂O surface water : 24-672; Half-life (hr) H₂O ground : 336-8640; Half-life (hr) soil : 52-672; Henry's Pa m³/mol : 637-879; Henry's atm m³ /mol - 7.68E-03; BOD 5 if unstated - 1.4, 1%; COD - 2.56, 13% ThOD - 3.125 : BCF : 23; log BCF : 1.17-2.41.

Environmental Fate: Most xylenes released to the environment will occur in the atmosphere and volatilisation is the dominant environmental fate process. Soil - Xylenes are expected to have moderate mobility in soil evaporating rapidly from soil surfaces.

DO NOT discharge into sewer or waterways.

12.2 Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
n-butanol	LOW (Half-life = 54 days)	LOW (Half-life = 3.65 days)
xylene	HIGH (Half-life = 360 days)	LOW (Half-life = 1.83 days)

12.3 Bioaccumulation potential

Ingredient	Bioaccumulation
n-butanol	LOW (BCF = 0.64)
xylene	MEDIUM (BCF = 740)
zinc oxide	LOW (BCF = 217)

12.4 Mobility in soil

Ingredient	Mobility
n-butanol	MEDIUM (KOC = 2.443)

12.5 Results of PBT and vPvB assessment

	P	B	T
Relevant available data	Not Available	Not Available	Not Available
PBT	X	X	X
vPvB	X	X	X

PBT Criteria fulfilled?	No
vPvB	No

12.6 Endocrine Disruption Properties

The evidence linking adverse effects to endocrine disruptors is more compelling in the environment than it is in humans. Endocrine disruptors profoundly alter reproductive physiology of ecosystems and ultimately impact entire populations. Some endocrine-disrupting chemicals are slow to break-down in the environment. That characteristic makes them potentially hazardous over long periods of time. Some well established adverse effects of endocrine disruptors in various wildlife species include; eggshell-thinning, displayed of characteristics of the opposite sex and impaired reproductive development. Other adverse changes in wildlife species that have been suggested, but not proven include; reproductive abnormalities, immune dysfunction and skeletal deformities.

12.7. Other adverse effects

Not Available

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product / packaging disposal:	<p>Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible.</p> <p>Otherwise:</p> <p>If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</p> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>DO NOT allow wash water from cleaning or process equipment to enter drains.</p> <p>It may be necessary to collect all wash water for treatment before disposal.</p> <p>In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</p> <p>Removal of bisphenol A (BPA) from aqueous solutions was accomplished by adsorption of enzymatically generated quinone derivatives on chitosan beads. The use of chitosan in the form of beads was found to be more effective because heterogeneous removal of BPA with chitosan beads was much faster than homogeneous removal of BPA with chitosan solutions, and the removal efficiency was enhanced by increasing the amount of chitosan beads dispersed in the BPA solutions and BPA was completely removed by quinone adsorption in the presence of chitosan beads more than 0.10 cm³/cm³. In addition, a variety of bisphenol derivatives were completely or effectively removed by the procedure constructed in this study, although the enzyme dose or the amount of chitosan beads was further increased as necessary for some of the bisphenol derivatives used.</p> <p>Recycle wherever possible.</p> <p>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or</p>
--------------------------------------	--

	disposal facility can be identified. Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
Waste treatment options:	Not available.
Sewage disposal options:	Not available.

14. TRANSPORT INFORMATION

Labels required:



Marine Pollutant:

Hazchem:

3Y

Land transport (ADR):

14.1 UN number	1263
14.2 UN proper shipping name	PAINT or PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	Class: 3 Subrisk: N/A
14.4 Packing group	III
14.5 Environmental hazard	Environmentally hazardous
14.6 Special precautions for user	Hazard identification (Kemler): 30 Classification code: F1 Hazard label: 3 Special provisions: 163 367 650 Limited quantity: 5 L Tunnel restriction code: 3 (D/E) (E)

Air transport (ICAO-IATA/DGR):

14.1 UN number	1263
14.2 UN proper shipping name	Paint (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base)
14.3 Transport hazard class(es)	ICAO/IATA class: 3 ICAO/IATA subrisk: N/A ERG code: 3L
14.4 Packing group	III
14.5 Environmental hazard	Environmentally hazardous
14.6 Special precautions for user	Special provisions: A3 A72 A192 Cargo only packing instruction: 366 Cargo only maximum qty/pack: 220 kg Passenger and cargo packing instruction: 355 Passenger and cargo maximum qty/pack: 60 L Passenger and cargo limited qty packing instructions: Y344 Passenger and cargo limited maximum qty/pack: 10 L

Sea transport (IMDG-Code/GGVSee):

14.1 UN number	1263
14.2 UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
14.3 Transport hazard class(es)	IMDG class: 3 IMDG subrisk: Not Applicable
14.4 Packing group	III
14.5 Environmental hazard	Marine Pollutant
14.6 Special precautions for user	EMS number: F-E , S-E Special provisions: 163 223 367 955 Limited quantities: 5 L

Inland waterways transport (ADN):

14.1 UN number	1263
14.2 UN proper shipping name	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)
14.3 Transport hazard class(es)	Class: 3 Subrisk: N/A
14.4 Packing group	III
14.5 Environmental hazard	Environmentally hazardous
14.6 Special precautions for user	Classification code: F1 Special provisions: 163; 367; 650 Limited quantity: 5 L Equipment required: PP, EX, A Fire cones numbers: 0

14.7. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.8. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product Name	Group
naphtha petroleum, light aromatic solvent	Not Available
n-butanol	Not Available
bisphenol A/ bisphenol A diglycidyl ether polymer	Not Available
zinc phosphate	Not Available
xylene	Not Available
zinc oxide	Not Available
fatty acids, C18-unsatd., trimers, compds. with oleylamine	Not Available
fatty acids, tall-oil, compounds with oleylamine	Not Available

14.9. Transport in bulk in accordance with the ICG Code

Product Name	Group
naphtha petroleum, light aromatic solvent	Not Available
n-butanol	Not Available
bisphenol A/ bisphenol A diglycidyl ether polymer	Not Available
zinc phosphate	Not Available
xylene	Not Available
zinc oxide	Not Available
fatty acids, C18-unsatd., trimers, compds. with oleylamine	Not Available
fatty acids, tall-oil, compounds with oleylamine	Not Available

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

naphtha petroleum, light aromatic solvent is found on the following regulatory lists:

Chemical Footprint Project - Chemicals of High Concern List	Europe EC Inventory
EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)
EU REACH Regulation (EC) No 1907/2006 - Annex XVII (Appendix 2) Carcinogens: category 1B (Table 3.1)/category 2 (Table 3.2)	European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI
EU REACH Regulation (EC) No 1907/2006 - Annex XVII (Appendix 4) Mutagens: category 1B (Table 3.1)/category 2 (Table 3.2)	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

n-butanol is found on the following regulatory lists:

EU European Chemicals Agency (ECHA) Community Rolling Action Plan (CoRAP) List of Substances	European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)
EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI
Europe EC Inventory	

bisphenol A/ bisphenol A diglycidyl ether polymer is found on the following regulatory lists:

Chemical Footprint Project - Chemicals of High Concern List	
---	--

zinc phosphate is found on the following regulatory lists:

EU European Chemicals Agency (ECHA) Community Rolling Action Plan (CoRAP) List of Substances	European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)
Europe EC Inventory	European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

xylene is found on the following regulatory lists:

EU Consolidated List of Indicative Occupational Exposure Limit Values (IOELVs)	European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)
EU European Chemicals Agency (ECHA) Community Rolling Action Plan (CoRAP) List of Substances	European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI
EU REACH Regulation (EC) No 1907/2006 - Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
Europe EC Inventory	

zinc oxide is found on the following regulatory lists:

EU European Chemicals Agency (ECHA) Community Rolling Action Plan (CoRAP) List of Substances	European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)
Europe EC Inventory	European Union (EU) Regulation (EC) No 1272/2008 on Classification, Labelling and Packaging of Substances and Mixtures - Annex VI

fatty acids, C18-unsatd., trimers, compds. with oleylamine is found on the following regulatory lists:

Not Applicable	
----------------	--

fatty acids, tall-oil, compounds with oleylamine is found on the following regulatory lists:

Europe EC Inventory	European Union - European Inventory of Existing Commercial Chemical Substances (EINECS)
---------------------	---

This safety data sheet is in compliance with the following EU legislation and its adaptations - as far as applicable - : Directives 98/24/EC, - 92/85/EEC, - 94/33/EC, - 2008/98/EC, - 2010/75/EU; Commission Regulation (EU) 2020/878; Regulation (EC) No 1272/2008 as updated through ATPs.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

ECHA SUMMARY

Ingredient	CAS number	Index No	ECHA Dossier
naphtha petroleum, light aromatic solvent	64742-95-6	649-356-00-4	01-2119486773-24-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Flam. Liq. 3; Asp. Tox. 1; Skin Irrit. 2; Eye Irrit. 2; Resp. STOT SE 3; Narc. STOT SE 3; Aquatic Chronic 2	GHS02; GHS09; GHS08; GHS07; Dgr	H226; H304; H315; H319; H335; H336
2	Flam. Liq. 3; Asp. Tox. 1; Skin Irrit. 2; Eye Irrit. 2; Resp. STOT SE 3; Narc. STOT SE 3; Aquatic Chronic 2	GHS02; GHS09; GHS08; GHS07; Dgr	H226; H304; H315; H319; H335; H336; H411
1	Asp. Tox. 1; Mut. 1B; Carc. 1B	GHS08; Dgr	H304; H340; H350

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

2	Asp. Tox. 1; Flam. Liq. 1; Skin Irrit. 2; Narc. STOT SE 3; Repr. 2; Aquatic Chronic 2; Eye Irrit. 2; Resp. STOT SE 3; Muta. 1A; Acute Tox. 4; Aquatic Acute 1; Carc. 1A; Acute Tox. 4; STOT RE 1	GHS08; Dgr; GHS02; GHS09; GHS07; None Specified	H304; H224; H315; H336; H361; H411; H335; H318; H340; H332; H350; H302; H372
---	--	---	--

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
n-butanol	71-36-3	603-004-00-6	01-2119484630-38-XXXX 01-2120076484-50-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Dam. 1; Resp. STOT SE 3; Narc. STOT SE 3	GHS02; GHS05; GHS07; Dgr	H226; H302; H315; H318; H335; H336
2	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Eye Dam. 1; Resp. STOT SE 3; Narc. STOT SE 3; Acute Tox. 4; Acute Tox. 2; Asp. Tox. 1; STOT RE 1	GHS02; GHS05; GHS07; Dgr; GHS08; Wng	H302; H315; H318; H335; H336; H370; H332; H225; H304; H372

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
bisphenol A/ bisphenol A diglycidyl ether polymer	25036-25-3	Not Available	Not Available

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Skin Sens. 1; Skin Irrit. 2; Eye Irrit. 2	GHS07; Wng	H317; H315; H319
2	Skin Sens. 1; Eye Irrit. 2; Skin Irrit. 2; Aquatic Chronic 2; Resp. STOT SE 3; Aquatic Acute 1; Acute Tox. 4	GHS07; Wng; GHS09	H317; H319; H315; H411; H335; H400; H332

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
zinc phosphate	7779-90-0	030-011-00-6	01-2119485044-40-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Aquatic Acute 1; Aquatic Chronic 1	GHS09; Wng	H400; H410
2	Aquatic Acute 1; Aquatic Chronic 1	GHS09; Wng	H400; H410
1	Aquatic Acute 1; Aquatic Chronic 1	GHS09; Wng	H410
2	Aquatic Acute 1; Aquatic Chronic 1	GHS09; Wng	H410; H400

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
xylene	1330-20-7	601-022-00-9	01-2119488216-32-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Flam. Liq. 3; Acute Tox. 4; Skin Irrit. 2; Acute Tox. 4	GHS02; GHS07; Wng	H226; H312; H315; H332
2	Acute Tox. 4; Skin Irrit. 2; Acute Tox. 4; Asp. Tox. 1; Eye Irrit. 2; Resp. STOT SE 3; Narc. STOT SE 3; Aquatic Chronic 2; Repr. 1B; STOT SE 1; STOT RE 1; Flam. Liq. 2; Acute Tox. 4; Lact.; Aquatic Acute 1; Asp. Tox. 2	GHS02; GHS07; Wng; GHS08; Dgr; GHS01; GHS09	H312; H315; H332; H304; H335; H336; H411; H360; H370; H372; H225; H302; H318; H362; H400

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
zinc oxide	1314-13-2	030-013-00-7	01-2119463881-32-XXXX 01-2120089607-43-XXXX 01-2119485288-24-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Aquatic Acute 1; Aquatic Chronic 1	GHS09; Wng	H410
2	Aquatic Acute 1; Aquatic Chronic 1; Repr. 1A; Resp. STOT SE 3; STOT SE 1; STOT RE 1; Acute Tox. 2; Acute Tox. 2; Skin Sens. 1; Eye Dam. 1; Muta. 2; Carc. 1A; Skin Corr. 1B	GHS09; Wng; GHS08; GHS07; Dgr; GHS06; GHS05	H410; H360; H400; H335; H370; H372; H300; H330; H317; H318; H341; H350; H314
1	Acute Tox. 4; Eye Dam. 1; Acute Tox. 4; Carc. 1A; Repr. 1A; Lact.; STOT RE 1; Aquatic Acute 1; Aquatic Chronic 1	GHS09; GHS08; GHS05; GHS07; Dgr	H302; H332; H315; H318; H350; H360; H373; H410
2	Acute Tox. 4; Eye Dam. 1; Acute Tox. 4; Carc. 1A; Repr. 1A; Lact.; STOT RE 1; Aquatic Acute 1; Aquatic Chronic 1	GHS09; GHS08; GHS05; GHS07; Dgr	H302; H332; H315; H318; H350; H360; H373; H410
1	Not Classified	Not Available	Not Available
2	Not Classified	Not Available	Not Available

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
fatty acids, C18-unsatd., trimers, compds. with oleylamine	147900-93-4	Not Available	01-2119971821-33-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Skin Irrit. 2; Aquatic Chronic 2	GHS09; GHS07; Wng	H315; H411
2	Acute Tox. 4; Skin Sens. 1; Aquatic Chronic 2; Skin Irrit. 2; STOT RE 1	GHS09; GHS08; Wng; GHS07; Dgr	H317; H411; H315; H302; H372

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
fatty acids, tall-oil, compounds with oleylamine	85711-55-3	Not Available	01-2119974148-28-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Acute Tox. 4; Skin Irrit. 2; Skin Sens. 1B; Aquatic Chronic 4	GHS07; Wng	H302; H315; H317; H413
2	Eye Dam. 1; STOT RE 2; Acute Tox. 4; Skin Irrit. 2; Aquatic Chronic 4; Skin Sens. 1	GHS08; GHS05; Dgr; GHS07; Wng	H318; H373; H302; H315; H413; H317

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

National Inventory	Status
Australia - AIIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (naphtha petroleum, light aromatic solvent; n-butanol; bisphenol A/ bisphenol A diglycidyl ether polymer; xylene; fatty acids, C18-unsatd., trimers, compds. with oleylamine; fatty acids, tall-oil, compounds with oleylamine)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (bisphenol A/ bisphenol A diglycidyl ether polymer; fatty acids, C18-unsatd., trimers, compds. with oleylamine)
Japan - ENCS	No (fatty acids, C18-unsatd., trimers, compds. with oleylamine; fatty acids, tall-oil, compounds with oleylamine)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	No (fatty acids, C18-unsatd., trimers, compds. with oleylamine; fatty acids, tall-oil, compounds with oleylamine)
USA - TSCA	Yes
Taiwan - TCSI	Yes

Mexico - INSQ	No (bisphenol A/ bisphenol A diglycidyl ether polymer; zinc phosphate; fatty acids, C18-unsatd., trimers, compds. with oleylamine; fatty acids, tall-oil, compounds with oleylamine)
Vietnam - NCI	Yes
Russia - FBEPH	No (fatty acids, C18-unsatd., trimers, compds. with oleylamine; fatty acids, tall-oil, compounds with oleylamine)
Legend:	Yes = All CAS declared ingredients are on the inventory. No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets).

16. OTHER INFORMATION

Full text Risk and Hazard codes

H224: Extremely flammable liquid and vapour.
H226: Flammable liquid and vapour.
H300: Fatal if swallowed.
H302: Harmful if swallowed.
H304: May be fatal if swallowed and enters airways.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H319: Causes serious eye irritation.
H330: Fatal if inhaled.
H332: Harmful if inhaled.
H340: May cause genetic defects.
H341: Suspected of causing genetic defects.
H350: May cause cancer.
H360: May damage fertility or the unborn child.
H361: Suspected of damaging fertility or the unborn child.
H362: May cause harm to breast-fed children.
H370: Causes damage to organs.
H372: Causes damage to organs through prolonged or repeated exposure.
H373: May cause damage to organs through prolonged or repeated exposure.
H400: Very toxic to aquatic life.
H410: Very toxic to aquatic life with long lasting effects.
H413: May cause long lasting harmful effects to aquatic life.

SDS Version Summary

Version	Date of Update	Section Updated
2.0	01/08/2023	Template Change

Other information:

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

For detailed advice on Personal Protective Equipment, refer to the following EU CEN Standards:

EN 166 Personal eye-protection
EN 340 Protective clothing
EN 374 Protective gloves against chemicals and micro-organisms
EN 13832 Footwear protecting against chemicals
EN 133 Respiratory protective devices

Definitions and abbreviations:

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit.
IDLH: Immediately Dangerous to Life or Health Concentrations
ES: Exposure Standard

Our company policy is one of continuous research and development; we therefore reserve the right to amend content herein without prior notice.

OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index
AIIIC: Australian Inventory of Industrial Chemicals
DSL: Domestic Substances List
NDSL: Non-Domestic Substances List
IECSC: Inventory of Existing Chemical Substance in China
EINECS: European Inventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory
NZIoC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances
TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory.
INSQ: Inventario Nacional de Sustancias Químicas
NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

The contents and format of this SDS are in accordance with EEC Commission Directive 1999/45/EC, 67/548/EC, 1272/2008/EC and EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

