

Product Datasheet

Alumasc Polyester Protection Fleece

Sheet No: PDS-AP008
Issued: Dec 2025
Pages: 1 of 1

Description

Alumasc Polyester Protection Fleece is a non-woven polyester material that is resistant to rot, bitumen, and bacterial deterioration. It is designed to provide physical protection and separation between adjacent surfaces.

Applications which require a chemical separation / compatibility separation, should use Alumasc Separation Fleece.

Application

Used as a protective layer positioned either above or beneath the Aluply PVC Single Ply membrane. Side and end laps must be formed with a minimum overlap of 100 mm. The fleece is loose-laid in horizontal applications; however, mechanical fixing may be required when installed on vertical surfaces.

Product Data

Sheet Length	75m
Sheet Width	2.2m
Colour	White
Mass	300 (g/m ²)
Thickness	3mm
Roll Weight	49.5 Kgs

Fire Performance

Reaction to Fire: Class A in accordance with EN 13501-1.

Storage

Store horizontally in the original packaging, in a clean, dry location, away from heat sources.

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.
Hygiene, Health and Environment - The product does not contain substances known to be harmful to human health or the environment under normal conditions of use and complies with applicable Health and Safety requirements.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400
Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.