

Product Datasheet

Aluply PVC Metal

Sheet No: PDS-AP011
Issued: Jan 2026
Pages: 1 of 1

Description

Aluply PVC Metal is a galvanized steel flat sheet coated with a proprietary coating of the Aluply PVC compound to ensure a seamless bond between the flexible sheets and the rigid metal. The product is used to manufacture custom made finishing elements such as roof flashings and terminations. The material is supplied in flat sheet form.

Application

Trims and Flashings should be fastened in accordance with the details contained within the projects specification. Allow for a gap of 5mm between adjoining sections Aluply PVC Metal for expansion. The joints must be taped with 50mm wide aluminium tape. The joints are then to be concealed using a 200mm wide strip of Aluply Reinforced Membrane centred over the joint.

Storage

Store horizontally in the original packaging, in a clean, dry location, away from heat sources.

Product Data

General Data	Detail
Sheet Length	2m
Sheet Width	1m
Colour	RAL 7016 – Anthracite Grey
Total Thickness	1.8mm
PVC Coating	1.2mm
Steel Sheet Thickness	0.6mm
Mass	6.0

Fire Performance

Reaction to Fire – Class A.

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400
Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.