

# Product Datasheet

## Aluply PVC Metal

Sheet No: PDS-AP011  
Issued: Dec 2025  
Pages: 1 of 1

### Description

Aluply PVC Metal is a galvanised steel flat sheet coated with a proprietary Aluply PVC compound, developed to ensure a secure and seamless bond between the flexible PVC-P membrane and the rigid metal substrate. The product is used in the fabrication of bespoke finishing components such as roof flashings, trims, and termination details. Aluply PVC Metal is supplied in flat sheet form for on-site or off-site fabrication.

### Application

Trims and flashings shall be fastened in accordance with the details contained within the project specification. A minimum 5mm expansion gap must be allowed between adjoining sections of Aluply PVC Metal. All joints are to be temporarily sealed using 50mm wide aluminium tape. The joints shall then be concealed by welding a 200mm wide strip of Aluply Reinforced Membrane, centrally positioned over the joint.

### Product Data

Sheet Length	2m
Sheet Width	1m
Colour	Black
Total Thickness	1.8mm
PVC Coating	1.2mm
Steel Sheet Thickness	0.6mm
Mass	6.0

### Fire Performance

Reaction to Fire: Class A in accordance with EN 13501-1.

### Storage

Store horizontally in the original packaging, in a clean, dry location, away from heat sources.

### Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from [www.alumascroofing.com](http://www.alumascroofing.com).

### Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: [technical@alumascroofing.com](mailto:technical@alumascroofing.com)

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.