

Product Datasheet

Aluply Fixing Bar

Sheet No: PDS-AP012
 Issued: Dec 2025
 Pages: 1 of 1

Description

Aluply Fixing Bar is a high-grade galvanised steel bar supplied with pre-drilled holes to accommodate fasteners or tube washers, as required by the application, at predetermined centres.

Application

- Termination of membrane at parapet walls and penetrations.
- Peel stop details on bonded membrane systems.
- An alternative to load spreading pressure plates in a mechanically attached roof system.

Site cut bar ends should be wrapped with membrane or tape to prevent damage to the membrane.

Product Data

Material	Galvanized Steel
Height (mm)	30mm
Width (mm)	30mm
Length (y) (m)	2.1m
Thickness (mm)	1.5mm
Weight Per 2.1m Bar	0.72 Kg
Pack Content	10 Lengths



30mm wide x
1.2mm thick
4.5mm leg height



Pre-Drilled Hole Centres

6.5mm Ø hole for fasteners at 100mm centres.

15mm Ø hole for Tube Washers at 100mm centres.

Storage

Store dry. Packs should be laid flat in original packing where possible, do not stack in cross form or under pressure.

Health & Safety

Safety Data Sheets are available upon request and can also be downloaded directly from www.alumascroofing.com.

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Email: technical@alumascroofing.com

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.