

Product Datasheet

Roof-Pro ProDrain Parapet Roof Outlet

Sheet No: PDS-OUT008 [A]

Issued: 06/2026

Pages: 1 of 2

Description

Roof-Pro Stainless Steel Outlets are a rigid outlet with factory applied Single Ply or PVC membrane flange to ensure a guaranteed seal between the outlet body and membrane flange and a compatible seal between the outlet and the Single Ply or PVC roof membrane. Supplied with Alumasc Universal Leaf Guard if required.

Application

- Rainwater outlets specifically designed for use in through-wall applications or parapets

Key Features

- High quality 600mm long spigot manufactured from durable stainless steel
- Factory bonded flange to match specific membrane material being used (material must be specified at time of order)
- Membrane attached to the outlet allows for easy installation
- Suitable for use in new build or refurbishment applications



Code	Membrane type	Membrane size	Spigot Width (mm)	Spigot Height (mm)	Spigot Length (mm)	Flow rates (l/s)*
PRO-DRAIN-SQ-215 PVC DK GREY	PVC dark grey	445 x 298	215	70	600	2.02
PRO-DRAIN-SQ-215 PVC LT GREY	PVC light grey	445 x 298	215	70	600	2.02
PRO-DRAIN-SQ-215 SBS	SBS	700 x 500	215	70	600	2.02
PRO-DRAIN-SQ-300 PVC LT GREY	PVC light grey	530 x 328	300	100	600	2.76
PRO-DRAIN-SQ-300 PVC DK GREY	PVC dark grey	530 x 328	300	100	600	2.76
PRO-DRAIN-SQ-300 SBS	SBS	900 x 500	300	100	600	2.76
PRO-DRAIN-SQ-500 PVC DK GREY	PVC dark grey	730 x 328	500	100	600	3.27
PRO-DRAIN-SQ-500 PVC LT GREY	PVC light grey	730 x 328	500	100	600	3.27
PRO-DRAIN-SQ-500 SBS	SBS	900 x 500	500	100	600	3.27

* As recommended by UK design standard BS EN 12056 : 3-2000 with a water depth of 35mm.


Product Datasheet

Roof-Pro ProDrain Parapet Roof Outlet

Sheet No: PDS-OUT008 [A]

Issued: 06/2026

Pages: 2 of 2



FO-PG-325



PRO-DRAIN-SQ-215-SBS

For use with the 215 and 300 wide option

For the 215 & 300 use the PG-325 Leaf Guard. For the 500 please speak to Customer Service or Technical.

Technical Support

Technical advice is available from Roof-Pro Technical Services at:

Telephone: +44 (0)1744 648400

Email: cad@roof-pro.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.