

Description

Eurorooft SA Primer applied by roller is a synthetic rubber-based primer, black in colour.

Use

For the preparation of new and existing substrates to promote adhesion of self-adhesive membranes

Application

- Ensure all preparation is complete and that surfaces are dry, clean, and free from contaminants.
- Stir well before use, until smooth. Apply by brush, roller and allow to dry completely.
- Open time is approx. 5 - 30 minutes, depending on ambient temperature and humidity; adjust as required to suit site conditions. The primer is ready to bond when it feels dry to the touch and does not transfer to gloved fingertips.
- Clean equipment with ethyl acetate or white spirit immediately after use.
- Do not use in conjunction with polystyrene foams.

Typical coverage rate is 4-8m²/L (100-200m² per 25 litre drum). Rough or porous surfaces may reduce the coverage rate.

Product Data

Packaging	25 litre drums
Storage	Store in a well-ventilated area, away from heat sources. Keep in airtight drums
Application	Roller or Brush
Flash Point	-18°C
Shelf-life	12 months if stored at a cool temperature in an unopened drum
Solids Content	32 – 36%
Application temperature	+5°C - 30°C

Health & Safety

Copies of Alumasc Safety Data Sheets can be downloaded from the Alumasc Roofing [website](#).