

## Description

Eurorooft SA Primer applied by spray is a synthetic rubber-based polymetric primer, black in colour. Requires spray gun & hose for application.

## Use

For the preparation of new and existing substrates to promote adhesion of self-adhesive membranes

## Application

### Canister set-up:

- Connect the hose to the spray wand, ensure the spray tip is fitted, and tighten the nut with a spanner.
- Remove the black cap on the canister valve and attach the hose to the valve and tighten the nut with a spanner.
- Once both nuts are tightened, secure open the valve on the top of the canister.
- Do not close canister valve until the canister is completely empty. To do so may cause the primer to block in the hose.
- On completion of works, turn the black valve on the spray wand clockwise until fully closed. Clean the end of the spray wand with **Eurorooft Solvent** ensuring that the aperture is clean. Once the canister is empty the hose to the canister valve can be removed and attached to a fresh canister.



1. Equipment required



2. Connect hose to the



3. Gently open the valve

### Adhesive set-up:

- Ensure all preparation is complete and that surfaces are dry, clean, and free from contaminants.
- Pull the trigger on the spray wand to begin spraying and adjust the spray width using the black control valve.
- Apply with the spray gun at 90° to the surface and apply evenly ensuring a continuous coat.
- Move the gun in parallel to the surface and pay particular attention to the edges. Do not allow the primer to puddle. On porous surfaces, it may be necessary to apply a second coat.
- Open time is approx. 2 - 15 minutes, depending on ambient temperature and humidity; adjust as required to suit site conditions. The primer is ready to bond when it feels dry to the touch and does not transfer to gloved fingertips.

Typical coverage rate is up to 300m<sup>2</sup> per canister. Rough or porous surfaces may reduce the coverage rate, and a second coat may be required in some instances.



4. Correct application of adhesive

## Product Data

|                         |                                                         |
|-------------------------|---------------------------------------------------------|
| Packaging               | 22 litre cannister                                      |
| Propellant              | Hydrocarbon                                             |
| Storage                 | Store in a well-ventilated area, away from heat sources |
| Solids Content          | 35 - 40%                                                |
| Application Temperature | +5 - 30°C                                               |

## Health & Safety

Copies of Alumasc Safety Data Sheets can be downloaded from the Alumasc Roofing [website](https://www.alumascroofing.com/downloads).