

Description

Euroroof SB Primer is a high penetration solvent based bitumen primer, black in colour.

Use

For the preparation of new and existing substrates to promote adhesion of bituminous membranes and hot melt systems.

Application

- Ensure all preparation is complete and that surfaces are dry, clean, and free from contaminants.
- Stir well before use, until smooth. Apply by brush, roller and allow to dry completely.
- Do not apply if there is any standing water or condensation.
- On metal surfaces all loose rust should be removed using a wire bristled brush, and where advanced signs of corrosion are evident, these areas should initially be treated with a rust inhibitor.
- Drying time is approx. 30 minutes and may vary depending on temperature and humidity at the time of installation. For cementitious surfaces, allow a minimum drying time of 2 hours before overcoating.
- Clean equipment with ethyl acetate or white spirit immediately after use.

Typical coverage rate is 7-10m²/L. Rough or porous surfaces may reduce the coverage rate.

Product Data

Packaging	25 litre drums
Storage	Store in a well-ventilated area, away from heat sources. Keep in airtight drums
Application	Roller or Brush
Flash point	39°C
Solids content	30 – 40%
Application temperature	+5°C - 30°C

Health & Safety

Copies of Alumasc Safety Data Sheets can be downloaded from the Alumasc Roofing [website](#).