

## Description

Caltech FCP SP Primer is a moisture curing primer for application to single ply for use with Alumasc's Caltech FCP System.

## Use

Caltech FCP SP Primer is suitable for use to TPO and EPDM single ply's, subject to adhesion tests (consult Alumasc Technical Services for details).

## Application

Due to the large number of single ply membranes, it is essential to carry out adhesion tests to determine suitability for coating prior to commencement of works.

For preparation and application guidance, please consult Alumasc specification.

## Product Data

|                         |                                                                                                                                                                                                                                                                              |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pack size               | 1 litre canister                                                                                                                                                                                                                                                             |
| Coverage                | 12-15m <sup>2</sup> /l                                                                                                                                                                                                                                                       |
| Typical Cure time       | 30-60 mins                                                                                                                                                                                                                                                                   |
| Application Temperature | 3°C* – 35°C<br>The substrate temperature must be at least 3°C above the dew point during application and curing.                                                                                                                                                             |
| Storage                 | Store the products sealed in their original airtight container and in a cool, dry and frost-free place. Direct sunlight on the containers should be avoided, including on site. After removing some of the contents, reseal the containers immediately so they are airtight. |
| Shelf-life              | 6 months if stored as above (unopened, once opened, the product may gel prematurely. Do not use any product that has gelled).                                                                                                                                                |

\*Coverage is approximate and may be affected by porosity and surface-type.

## Health & Safety

Copies of Alumasc Safety Data Sheets can be downloaded from the Alumasc Roofing [website](http://www.alumascroofing.com/downloads).