

Description

Caltech FCP Epoxy Primer is a two-component, fast-curing bonding primer with minimal odour.

Use

Suitable for concrete, timber, metal, masonry, fibre cement boards, and bituminous or asphalt waterproofing.

Application

It is essential to carry out adhesion tests to determine suitability for coating prior to commencement of works. For preparation and application guidance, please consult Alumasc specification.

Product Data

Packaging	4 litre (Base = 3 litre / Activator = 1 litre)
Colour(s)	Beige
Coverage	10-15m ² /litre*
Typical Cure time	Touch dry time (20°C): 30 mins Overcoating time: 2-4 hours (min.)
Application Temperature	5°C – 30°C
Storage	Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep container tightly closed. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully re-sealed and kept upright to prevent leakage.
Shelf-life	12 months if stored as above (unopened, once opened storage life is reduced).
Note: Data represented above are average values unless noted otherwise.	

*Coverage is approximate and may be affected by porosity and surface-type.

Health & Safety

Copies of Alumasc Safety Data Sheets can be downloaded from the Alumasc Roofing [website](#).