

Description

Eurorooft Detail Adhesive is a synthetic rubber adhesive.

Use

For use as a cold adhesive for bonding membranes to vertical details such as upstands, rooflight kerbs, ventilation pipes etc, in both new construction and refurbishment projects. Suitable for use with timber, metal, and concrete surfaces.

Application

- Surfaces must be clean, dry and free from contamination.
- To maximise the adhesion of the self-adhesive range of membranes: Apply direct to the substrate by brush or roller to produce an even coat.
- To adhere all other types of bituminous membrane: Apply direct to both the substrate and the reverse side of the membrane by brush or roller to produce an even coat.
- Avoid puddling the primer as this will cause uneven drying.
- The membrane must be applied only when the primer is dry. Cure times stated will vary with ambient temperature fluctuations.
- Firmly pressure roll the surface to achieve a continuous bond across the full width of the membrane.

Storage

Store in a clean, dry location, away from heat sources. The product must be stored at between 5°C and 25°C, in closed airtight containers.

Product Data

Appearance	Green liquid
Coverage rate**	2m ² /l
Application temperature	5-30°C
Cure time	Approx. 15 minutes, subject to ambient temperature fluctuations
Packaging:	15 litre drums
Shelf-life	12 months in an unopened container
Environmental	Non-flammable

** Coverage rate is approximate, depending on porosity and type of surface (two coats may be required on very porous surfaces).

Health & Safety

Copies of Alumasc Safety Data Sheets can be downloaded from the Alumasc Roofing [website](#).