

Description

Derbicoat Selfix HP Underlay is a self-adhesive, glass/polyester reinforced, modified bitumen underlay, with a self-adhesive underside protected by a polyethylene release film, and a fine sanded surface.

Use

Underlay for use in built-up roofing systems on both new-build and refurbishment projects.

Application

All surfaces to receive membrane must be clean and dry. Prime the substrate with Eurorof SA Primer.

Install with 100mm side and 150mm end laps. Before removing the release film, confirm that the membrane is correctly aligned, including all overlaps. Firmly pressure roll the surface to achieve a continuous bond across the full width of the membrane. Side and end laps shall be heat sealed to ensure that a visible bead of bitumen exudes from all laps.

The installer must undertake adhesion tests of all non-Alumasc materials to the primed substrate before application.

Install the membrane only when ambient temperatures are +5°C and rising.

Storage

Store upright in a clean, dry location, away from heat sources, between +5°C and +28°C until installation

Product Data

Thickness	2mm
Width	1m
Length	10m
Weight	2.5 kg/m ²
Weight per roll	25 kg

Store upright in a clean, dry location, and away from heat sources.

Performance Data

Tensile Strength – longitudinal	≥600 N/50mm
Tensile Strength – transverse	≥500 N/50mm
Elongation at break – longitudinal	≥ 35%
Elongation at break – transverse	≥ 35%
Cold Bending	-25°C
Shelf life	12 months

Health & Safety

Copies of Alumasc Safety Data Sheets can be downloaded from the Alumasc Roofing [website](#).