

1. IDENTIFICATION OF THE SUBSTRATE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name/designation: Bituminous Roofing Membranes.
The products covered in this data sheet are listed in the table in Section 3.3.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Roofing membrane.

1.3 Supplier details

Alumasc Building Products Ltd
White House Works, Bold Road, Sutton, St Helens, Merseyside, United Kingdom, WA9 4JG
Tel: +44 (0)1744 648400
e-mail: technical@alumascroofing.com

1.4 Emergency telephone number

Other emergency telephone numbers: Alumasc Building Products: +44(0) 1744 648400
(Mon-Thurs – 08.30-17.00 Fri – 08.30-16.00)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EU) 1272/2008:

CLP-Classification: The product is non-dangerous in accordance with Directive 1272/2008/EEC.
Not classified.

Classification according to EU Directives 67/548/EEC or 1999/45/EC:

Classification: The product is an article and is not subject of Directive 67/548/EEC or Directive 1999/45/EC.
Not classified.

2.2 Label elements

Labelling according to Regulation (EU) 1272/2008:

Not applicable.

2.3 Other hazards

Under normal conditions of use, this product is not expected to create any unusual emergency hazards. Due to product form, exposure to dusts and fumes is not expected to occur.

3. COMPOSITION AND INFORMATION ABOUT THE COMPONENTS

3.1 Substances

Not applicable, products are articles.

3.2 Mixtures

The products are not mixtures under the CLP Regulation (EC) No 1272/2008 but are considered to be articles. The products in the range consist of a reinforcing base material coated with bitumen and a surface finish. The base materials include polyester, glass/polyester and glass fibres in sheet form, some used in conjunction with aluminium foil. The bitumen coating may contain mineral filler and/or synthetic polymers. The fire performance cap sheets have an inert graphite coating on the upper surface of the base carrier, and the fire performance vapour control layers have a fire-retardant modified bitumen coating. The surface finish may be sand, talc, mineral granules or polymeric film.

Derbigum AR Cap Sheet:

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-ethylhexyl-(+)-(R)-2-(4-chloro-2-methylphenoxy)propionate	(CAS No.) 861229-15-4 (EC No) - (EC Index) -	< 0,3	Acute Tox. 4 (Oral), H302 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

3.3 Products covered

Product Name	Application			Finish	
	Self-adhesive	Torch	PU	Plain/Sanded	Mineral
Derbigum AR Cap Sheet		✓		✓	
Derbigum GC Cap Sheet		✓		✓	
Derbigum Mineral Cap Sheet		✓			✓
Derbigum Olivine Cap Sheet		✓			✓
Derbigum Black Cap Sheet		✓		✓	
Derbigum Black FM Cap Sheet		✓		✓	
Derbicoat HP Selfix Underlay	✓			✓	
Derbicoat HP SKT Venting Underlay	✓			✓	
Derbicoat NT Underlay		✓		✓	
Derbigum NT Cap Sheet		✓		✓	
Hi-Ten Universal Underlay		✓		✓	
Derbicoat Alu AVCL		✓		✓	
Derbicoat Alu Selfix AVCL	✓			✓	
Eurorooft Torch-On Underlay		✓		✓	
Eurorooft Torch-On Cap Sheet		✓			✓
Eurorooft Self-Adhesive Venting Underlay	✓			✓	
Eurorooft Mono Cap Sheet			✓		✓
Eurorooft Rapid Cap Sheet		✓			✓
Eurorooft Self-Adhesive Cap Sheet	✓				✓
Eurorooft Self-Adhesive Underlay	✓			✓	
Eurorooft Self-Adhesive AVCL	✓			✓	
Eurorooft Premium Cap Sheet		✓			✓
Eurorooft Premium Underlay		✓		✓	
Eurorooft Torch-On AVCL		✓		✓	
Alumasc Exp Torch-On Cap Sheet		✓			✓
Alumasc Exp Torch-On AR Cap Sheet		✓			✓
Alumasc Exp Torch-On AR Cap Sheet (Sanded)		✓		✓	

Product Name	Application			Finish	
	Self-adhesive	Torch	PU	Plain/Sanded	Mineral
Alumasc Exp Torch-On AVCL		✓		✓	
Alumasc Exp Underlay		✓		✓	
Eurorof Torch-On AR Cap Sheet		✓			✓
Eurorof Premium AR Cap Sheet		✓			✓
Caltech Preparation Layer	✓			✓	

Product Name	Application	Finish	
	Hot-Melt	Plain/Sanded	Mineral
Hydrogard 20 Protection Sheet	✓	✓	
Hydrogard 20-AR Protection Sheet	✓	✓	
Hydrogard 40M-AR Protection Sheet	✓		✓

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye Contact:	For contact with cold material, e.g. small particles, wash thoroughly with water and obtain medical attention if signs of discomfort persist. In case of contact with hot material, flood eye with copious quantities of cold water for 10-15 minutes. Do not try to remove material adhering to the eye. Cover the burn area loosely with a sterile dressing, if available. Seek immediate medical attention.
Skin Contact:	For contact with hot material, cool the affected area under cold running water for at least 10 minutes. Do not attempt to remove anything from the burn area or apply burn creams or ointments. Material adhering to skin will form a sterile barrier which will fall off after a few days. Cover the burn area loosely with a sterile dressing, if available. Seek immediate medical attention.
Inhalation:	In case of inhalation of fumes, remove from exposure. If breathing becomes difficult, put victim at rest, cover with a blanket and keep warm, seek medical assistance.
Ingestion:	No adverse effects are expected. If swallowed, rinse mouth with water (only if the person is conscious). Get medical advice/attention if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Eyes:	Particulates produced from cutting, grinding or drilling of the product may cause mechanical irritation of the eye. Hot melt products may cause thermal burns.
Skin:	This product may produce skin abrasions. Mechanical rubbing may increase skin irritation. Hot melt products may cause thermal burns.
Ingestion:	Not a likely route of entry.
Inhalation:	Inhalation of dusts produced during cutting, grinding or sanding of this product or fumes from hot melt products may cause irritation of the mouth and nose and coughing.

4.3 Indication of any immediate medical attention and special treatments needed

When in doubt or if symptoms are observed, get medical advice.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media:

Extinguishing powder, Carbon dioxide, Sand.

Extinguishing media which must not be used for safety reasons:

Strong water jet.

5.2 Special hazards arising from the substance or mixture

Fire hazard: The product is not flammable.

Specific hazards: Evacuate area. When heated to decomposition, emits toxic fumes. Do not allow run-off from firefighting to enter drains or water courses. Dispose according to legislation.

5.3 Advice for fire-fighters

Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Fire-fighters should avoid inhaling any combustion products. Do not release chemically contaminated water into drains, soil or surface water.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: None usually necessary. If there are significant quantities of dust/shavings use personal protective equipment as required. Reference to other Sections: 8. Evacuate area. Avoid contact with skin and eyes. Avoid breathing dust or vapour. Provide adequate ventilation. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

For emergency responders: Ensure procedures and training for emergency decontamination and disposal are in place. Reference to other Sections: 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and materials for containment and cleaning up

Sweep up or gather material and place in appropriate container for disposal. Dispose according to legislation.

6.4 References to other sections

See Sections 8 and 13 for further advice on protective clothing and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Customary personal hygiene measures, such as washing hands after working with these products are recommended. If dusts or fumes of this product are generated, avoid inhalation, skin and eye contact. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Room temperature - normal conditions. Warehouse storage should be in accordance with package directions. Material should be kept dry and protected from the elements.

7.3 Specific end uses(s)

No special requirements.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

If process generated dusts or fumes are likely, follow workplace regulatory exposure limits for relevant hazards.

Asphalt (8052-42-4)		
UK (EH40)	8-hour TWA	5 mg/m ³ (petroleum fumes, inhalable fraction)
UK (EH40)	15-minute reference period	10 mg/m ³ (petroleum fumes, inhalable fraction)
UK (EH40)	Biological Monitoring Guidance Value for polycyclic aromatic hydrocarbons (PAHs)	4 µmol 1-hydroxypyrene/mol creatinine in urine

Talc (14807-96-6)		
UK (EH40)	8-hour TWA	1 mg/m ³ (respirable fraction)

Nuisance dust		
UK (EH40)	8-hour TWA	10 mg/m ³ (inhalable fraction)
UK (EH40)	15-minute reference period	4 mg/m ³ (respirable fraction)

Silicon dioxide (7631-86-9)		
UK (EH40)	8-hour TWA (amorphous silica)	6 mg/m ³ (inhalable fraction)
UK (EH40)	15-minute reference period	2.4 mg/m ³ (respirable fraction)

- Silica is present as a constituent of the sand and mineral slate surfaced finishes used.
- Talc is present as a surface finish.
- Glass fibre is present as a reinforcing base encapsulated in bitumen. Exposure levels are likely to be very low in normal use.
- All products listed above contain bitumen.

8.2 Exposure controls

Engineering controls:

No special protective measures are necessary for use of this product in that it is an article, and under normal conditions of use is not expected to release or otherwise result in exposure to a hazardous chemical. If cutting, grinding, drilling, etc. ensure that there is adequate ventilation to keep dust levels within required limits.

Personal protective equipment:

Eyes/Face:	Where there is a risk of damage to the eyes/face from splashing of hot product or impact, wear eye/face protection to EN166.
Skin:	The use of heavy-duty gloves to protect against skin abrasion and burns through contact with hot bitumen or flame of gas torch during installation is recommended. Protective gloves complying with EN 374. & EN 407.
Respiratory:	Not required under normal conditions of use. If dust or fumes are generated, wear appropriate respiratory protection. Full face mask (EN 136), Half-face mask (DIN EN 140), Filter type: A (EN141).
Environmental Exposure Controls:	Not usually required.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance/Colour:	Grey – black toned solid material. A variety of coloured finishes are available on top layer felts.
Odour:	None.
Odour threshold:	Not applicable.
pH:	Not applicable.
Boiling point:	Not applicable.
Melting point:	150°C.
Flash point:	300°C.
Evaporation rate:	Not applicable.
Flammability (gas, solids):	Standard bitumen-based roofing membranes are combustible. Fire performance membranes have a significantly reduced capacity to burn.
Upper/Lower flammability limits:	Not applicable.
Vapour pressure:	Not applicable.
Relative density:	1,05.
Specific gravity:	Not applicable.
Solubility (H ₂ O):	Not soluble.
Solubility in other solvents:	Not applicable.
Auto ignition temperature:	350°C.
Decomposition temperature:	No data.
Viscosity:	Not applicable.
Explosive properties:	Not classified as explosive.
Oxidising properties:	Not classified as oxidising.

9.2 Other information

None.

10. STABILITY AND REACTIVITY

10.1 Reactivity

Not considered a reactive material.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

None expected.

10.4 Conditions to avoid

None identified.

10.5 Incompatible materials

None identified.

10.6 Hazardous decomposition products

Bitumen fumes and dense black smoke if heated to excessive temperatures. Burning produces noxious and toxic fumes. Hazardous decomposition products due to incomplete combustion. Carbon monoxide.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

This product has not been tested. Judgements on the expected toxicity of this product have been made based upon consideration of its major components.

- (a) **Acute toxicity** - not expected to present an acute toxicity hazard. Inhalation of fumes may result in irritation, especially if the product is overheated above recommended temperatures.

2-ethylhexyl-(+)-(R)-2-(4-chloro-2-methylphenoxy) propionate (861229-15-4)	
ATE CLP (oral)	500 mg/kg bodyweight

- (b) **Skin corrosion/irritation** - mechanical abrasion may occur in contact with skin. Thermal burns when handled at elevated temperatures.
- (c) **Serious eye damage/irritation** - not expected to present a hazard to the eyes. Mechanical irritation may occur in contact with particles. Thermal burns when handled at elevated temperatures.
- (d) **Respiratory/skin sensitisation** - not considered to be a skin or respiratory sensitizer
- (e) **Germ cell mutagenicity** - contains no components known to be mutagenic.
- (f) **Carcinogenicity** - Bitumen may contain substances including polyromantic hydrocarbons (PAHs), some types of which have been associated with cancer. However, long-term studies of bitumen and asphalt workers have not demonstrated any increased cancer risk from the use of these products, and bitumen has been classified by IARC as Group 3, not classifiable as to its carcinogenicity to humans.
- (g) **Reproductive toxicity** - contains no components known to be hazardous to reproduction.
- (h) **STOT-single exposure** - for Torch-on grades, inhalation of fumes may result in irritation, especially if the product is overheated above recommended temperatures.
- (i) **STOT-repeated exposure** - no chronic health effects are expected from the normal use of this product.
- (j) **Aspiration hazard** - not relevant.

12. ECOLOGICAL INFORMATION

These products have not been tested. Judgements on the expected toxicity of these products have been made based upon consideration of their major components.

12.1 Toxicity

Not expected to be toxic to the environment.

12.2 Persistence and degradability

Not expected to be biodegradable.

12.3 Bio accumulative potential

Not expected to bio accumulate.

12.4 Mobility in soil

Not expected to be mobile in the environment.

12.5 Results of PBT and vPvB assessment

Not applicable.

12.6 Other adverse effects

None known.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal Considerations:	Disposal of this product and its packaging must comply with all applicable environmental protection and waste disposal legislation, including any requirements set by local authorities. Any unwanted or non-recyclable material should be disposed of through a licensed waste disposal contractor. Transportation of such waste may be subject to ADR (International Carriage of Dangerous Goods by Road) regulations and must be managed in accordance with those requirements.
Waste code:	17 03 02 bituminous mixtures other than those mentioned in 17 03 01
Further information available via:	https://www.alumascroofing.com/downloads/disposal-guides/ 

14. TRANSPORT INFORMATION

Not considered to be dangerous goods for transport.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

All components are listed as existing substances in Europe.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

16. OTHER INFORMATION

Other information:

This safety data sheet is prepared in accordance with the formatting described in Commission Regulation (EU) No 453/2010.

Full text of R-, H- and EUH-phrases:

Acute Tox. 4 (Oral):	Acute toxicity Category 4.
Aquatic Acute 1:	Hazardous to the aquatic environment - Aquatic Acute 1.
Aquatic Chronic 1:	Hazardous to the aquatic environment - chronic hazard category 1.
Skin Sens. 1:	Skin sensitisation, hazard category 1.
H302:	Harmful if swallowed.
H317:	May cause an allergic skin reaction.
H400:	Very toxic to aquatic life.
H410:	Very toxic to aquatic life with long lasting effects.
R22:	Harmful if swallowed.
R43:	May cause sensitisation by skin contact.
R50/53:	Very toxic to aquatic organisms, may cause long-term adverse effects
N:	Dangerous for the environment
Xn:	Harmful

List of abbreviations used in this SDS:

CAS:	Chemical Abstracts Service.
CLP:	Classification, Labelling and Packaging Regulation (EC) no 1272/2008.
DSD:	Dangerous Substances Directive 67/548/EEC..
DPD:	Dangerous Preparations Directive 1999/45/EC
EC:	European Community/Commission.
PBT:	Persistent, Bioaccumulative and Toxic.
REACH:	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
vPvB:	very Persistent, very Bioaccumulative.

SDS version summary:

Version	Date of Update	Section Updated
2.0	27/05/2025	Section 13 update
2.1	03/09/2026	Removal of Eurorooft Olivine form product range

The contents and format of this SDS are in accordance with EEC Commission Regulation 1907/2006/EC (REACH) Annex II.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used onl